

Optimization of Warehouse Supply Chain Operations Using AI-Powered Smart Serving Robots

Aisha Rehman

Department of Physics, BEL Comsats University, Islamabad

Email: Ar877210@gmail.com

Tabish Qureshi

Upsource by Solutions (Solutions by STC) Masters of Computer Science - University of Karachi Email: Tabish.qureshi82@gmail.com

Shumaila Hussain

Assistant Professor SBKWU Quetta Email: Shumailahussain70@gmail.com

ABSTRACT

The rapid advancement of artificial intelligence and autonomous robotics has significantly transformed warehouse supply chain operations through intelligent automation and smart logistics systems. This study investigated the optimization of warehouse supply chain operations using AI-powered smart serving robots integrated with machine learning, computer vision, autonomous navigation, and embedded communication technologies. The developed robotic system utilized YOLOv4 object detection, convolutional neural networks, RRT* path planning, ultrasonic sensing, and NVIDIA Jetson TX2 embedded processing to perform autonomous material transportation, obstacle avoidance, and intelligent warehouse navigation. Experimental evaluation demonstrated that the robotic platform achieved reliable real-time object recognition, efficient collision-free navigation, stable communication performance, and adaptive operational coordination within simulated warehouse environments. The implementation of AI-driven navigation and autonomous delivery mechanisms significantly improved transportation efficiency, reduced operational delays, minimized manual workload, and enhanced warehouse logistics productivity. The findings further revealed that intelligent robotic systems can optimize route planning, improve obstacle handling, and support continuous supply chain operations with minimal human intervention. Despite challenges related to computational limitations and dynamic navigation complexity, the study concludes that AI-powered smart serving robots represent an effective solution for intelligent warehouse automation and Industry 4.0 logistics infrastructure. The research highlights the growing importance of autonomous robotic technologies in achieving efficient, reliable, and scalable warehouse supply chain optimization.

Keywords: AI-Powered Robots, Warehouse Automation, Smart Serving Robots, Autonomous Navigation, Supply Chain Optimization

Introduction

Warehouse supply chain operations have experienced substantial transformation with the emergence of Industry 4.0 technologies, particularly artificial intelligence, autonomous robotics, Internet of Things (IoT), and smart logistics systems. Traditional warehouse management systems heavily depended on manual labor for inventory transportation, sorting, material handling, and internal logistics operations, which often resulted in operational inefficiencies, increased labor costs, delayed deliveries, and inaccurate inventory management. The rapid growth of e-commerce platforms and increasing consumer demand for fast and accurate delivery services have intensified the need for intelligent warehouse automation systems capable of improving operational productivity and reducing human dependency. Industry 4.0 has accelerated the adoption of cyber-physical systems and AI-driven logistics technologies that enable warehouses to operate through autonomous decision-making, real-time monitoring, and intelligent process optimization. Smart logistics systems supported by machine learning and robotic automation have become essential components of modern supply chain infrastructure, enabling warehouses to improve efficiency, minimize operational errors, and enhance delivery performance. The integration of intelligent robotic systems within warehouse environments has significantly improved inventory handling, material transportation, and operational coordination while supporting continuous and data-driven logistics operations[1], [2], [3], [4].

Smart serving robots have emerged as advanced autonomous systems capable of optimizing warehouse operations through intelligent navigation, automated delivery, and real-time environmental interaction. These robots are designed to transport materials, move inventory, and perform delivery tasks within warehouse facilities with minimal human intervention. Autonomous robotic systems are increasingly utilized in modern warehouses to improve operational speed, reduce manual handling errors, and support high-volume logistics activities. Smart serving robots equipped with machine learning and embedded sensor technologies can independently navigate warehouse pathways, identify obstacles, transport products between storage and packaging areas, and execute delivery operations efficiently. The use of autonomous mobile robots in warehouse environments has significantly improved inventory movement accuracy and operational flexibility by reducing dependency on fixed infrastructure systems such as conveyor belts. Furthermore, robotic systems are capable of operating continuously without fatigue, enabling warehouses to maintain uninterrupted logistics activities and improve productivity during peak operational periods. Autonomous delivery mechanisms also allow robotic systems to optimize internal supply chain coordination by transporting goods directly to designated locations based on predefined operational commands and real-time environmental conditions. As warehouse operations continue to expand in complexity and scale, intelligent serving robots are becoming critical tools for achieving smart logistics automation and supply chain optimization[5], [6], [7], [8], [9], [10], [11].

Artificial intelligence and machine learning technologies play a central role in enhancing the intelligence, adaptability, and operational capabilities of autonomous warehouse robots. Machine learning algorithms enable robotic systems to process environmental information, identify objects, optimize navigation paths, and make

autonomous decisions in real time. Computer vision systems integrated with deep learning models such as YOLOv4 and convolutional neural networks allow robots to perform accurate object detection, environmental perception, and obstacle recognition during autonomous operation. These technologies enable robotic systems to identify inventory items, pathways, shelves, and operational targets while maintaining navigation safety within dynamic warehouse environments. Intelligent path planning algorithms such as Rapidly-exploring Random Trees (RRT*) further improve robotic navigation by generating optimized collision-free trajectories between operational points. Autonomous navigation systems continuously analyze environmental data collected through cameras, ultrasonic sensors, and embedded sensing devices to adapt movement strategies and avoid obstacles during operation. Reinforcement learning and predictive analytics also contribute to warehouse optimization by enabling robotic systems to learn from environmental interactions, improve route efficiency, and predict operational bottlenecks. Sensor fusion techniques integrating multiple sensing systems improve environmental awareness and navigation precision, allowing robots to operate effectively under varying warehouse conditions. The combination of artificial intelligence, machine learning, and embedded robotic systems significantly enhances warehouse operational efficiency, autonomous decision-making, and smart logistics performance[12], [13], [14], [15], [16], [17].

Despite the growing implementation of autonomous robotic systems in warehouse supply chain management, several operational and technical challenges continue to limit their overall efficiency and reliability. Traditional warehouse operations still suffer from manual inefficiencies associated with labor-intensive material handling, delayed inventory transportation, and inconsistent operational performance. Human-based warehouse logistics often result in increased processing time, inaccurate inventory placement, and reduced productivity, particularly in high-demand operational environments. Additionally, autonomous robotic systems encounter significant challenges related to navigation complexity, environmental uncertainty, and obstacle avoidance within crowded warehouse spaces. Dynamic warehouse environments contain moving workers, transport vehicles, temporary storage objects, and continuously changing operational layouts that complicate robotic navigation and autonomous movement. Existing robotic systems may experience navigation errors, delayed response times, and inefficient path planning when operating in highly dynamic environments. Real-time object detection and environmental perception also require substantial computational power, creating processing delays and reducing operational responsiveness in embedded robotic systems. Furthermore, sensor inaccuracies, communication latency, battery limitations, and insufficient integration between machine learning models and embedded control systems can negatively impact robotic performance and supply chain reliability. These limitations highlight the need for intelligent AI-powered robotic systems capable of adaptive navigation, efficient obstacle avoidance, real-time decision-making, and autonomous operational optimization in warehouse supply chain environments[18], [19], [20], [21], [22], [23], [24], [25], [26].

This study aims to investigate the role of AI-powered smart serving robots in optimizing warehouse supply chain operations through the integration of machine learning, autonomous navigation, object detection, and intelligent robotic automation.

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>

The study specifically evaluates how artificial intelligence technologies improve inventory transportation, warehouse logistics efficiency, and autonomous delivery performance within dynamic operational environments. The research further seeks to identify machine learning approaches implemented in warehouse robotic systems, evaluate the effectiveness of autonomous navigation and object detection technologies, analyze challenges affecting robotic operational performance, and propose technological improvements for future warehouse automation systems. Several research questions guide the study, including identifying the most effective machine learning models for autonomous warehouse robots, understanding how AI-driven robotic systems improve warehouse logistics efficiency, evaluating the role of autonomous navigation in supply chain optimization, and examining challenges associated with dynamic warehouse environments and real-time robotic operation[27], [28], [29].

The significance of this study lies in its contribution to the advancement of intelligent warehouse automation and AI-driven supply chain management systems. The research provides academic and practical insights into the integration of machine learning, computer vision, and autonomous robotics within warehouse operations. The findings are expected to support warehouse operators, logistics companies, and industrial automation developers in understanding the operational benefits and technical requirements of smart serving robotic systems. Additionally, the study contributes to the broader implementation of Industry 4.0 technologies by demonstrating how AI-powered robots can improve logistics efficiency, reduce operational costs, enhance inventory management, and support intelligent warehouse infrastructure. The research also provides a foundation for future developments in autonomous supply chain systems, smart logistics platforms, and intelligent robotic automation within modern industrial environments[30], [31], [32], [33].



Figure 1 AI-powered smart serving robots enabling autonomous warehouse logistics, intelligent navigation, and optimized supply chain operations in Industry 4.0 environments.

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>


Methodology

Experimental Research Design

This study adopted an experimental and development-based research methodology to investigate the optimization of warehouse supply chain operations using AI-powered smart serving robots. The research focused on the practical implementation and evaluation of an autonomous robotic system capable of object detection, intelligent navigation, obstacle avoidance, and automated material transportation within warehouse environments. The methodology integrated artificial intelligence algorithms, embedded robotic hardware, computer vision systems, and autonomous navigation frameworks to develop a robotic platform capable of operating with minimal human intervention. Unlike theoretical simulation-based approaches, the experimental methodology enabled real-time performance evaluation under warehouse operational scenarios. The research design emphasized autonomous functionality, operational efficiency, and machine learning integration to assess the effectiveness of AI-powered robotics in optimizing warehouse logistics, reducing manual workload, and improving supply chain performance.

Hardware Architecture

The hardware architecture of the robotic system consisted of multiple integrated components responsible for processing, sensing, movement control, and communication. The NVIDIA Jetson TX2 served as the primary processing unit due to its high computational capability and GPU support for machine learning applications. The Jetson TX2 executed object detection algorithms, image processing tasks, and autonomous navigation operations in real time. An ATmega328 microcontroller was integrated to control robotic movement, motor operations, and sensor coordination. Ultrasonic sensors (HC-SR04) were utilized for real-time obstacle detection and environmental sensing, enabling the robot to identify nearby obstacles and avoid collisions during autonomous navigation. A Logitech camera module was incorporated into the system for computer vision and object detection tasks, allowing the robot to capture environmental images and detect warehouse objects through machine learning algorithms. DC gear motors were used to execute movement commands generated by the navigation framework, enabling forward movement, directional turning, and autonomous delivery operations. The integration of these hardware components enabled the robotic system to perform autonomous warehouse transportation tasks with stable operational coordination and real-time



environm

ental interaction.

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>




Figure 2 Integrated hardware architecture comprising NVIDIA Jetson TX2, Atmega328 microcontroller, and HC-SR04 ultrasonic sensor for autonomous warehouse robotic operations.

AI Framework

The artificial intelligence framework implemented in this study was primarily based on the YOLOv4 object detection algorithm integrated with convolutional neural network architecture. YOLOv4 was selected due to its high-speed object detection capability and suitability for real-time warehouse robotic applications. The AI framework enabled the robot to perform object recognition, environmental perception, and obstacle identification during autonomous operation. The object detection system utilized computer vision techniques to identify warehouse pathways, operational targets, and surrounding obstacles in dynamic environments. Convolutional neural networks were employed for feature extraction and image classification to improve object recognition accuracy and environmental awareness. The AI implementation process included dataset preparation, image annotation, data augmentation, and model training to improve model generalization and operational reliability. The trained YOLOv4 model was deployed on the Jetson TX2 platform to support real-time inference and autonomous warehouse navigation. The integration of machine learning significantly improved robotic perception, autonomous decision-making, and intelligent logistics coordination within warehouse operational environments.

Autonomous Navigation

Autonomous navigation within the robotic system was implemented using the Rapidly-exploring Random Tree (RRT*) path planning algorithm. The RRT* algorithm enabled the robot to generate collision-free trajectories between predefined warehouse operational points while continuously adapting to dynamic environmental conditions. The navigation framework operated by randomly sampling environmental nodes, identifying nearest neighboring nodes, and optimizing movement trajectories to minimize travel distance and improve operational efficiency. Obstacle avoidance mechanisms were integrated into the navigation system using ultrasonic sensor feedback to detect nearby objects and prevent collisions during robotic movement. When obstacles were detected within predefined threshold distances, the system automatically recalculated movement paths to maintain safe navigation and operational continuity. The integration of RRT* path planning and obstacle avoidance significantly improved navigation efficiency, route optimization, and robotic adaptability within warehouse environments containing dynamic obstacles and changing operational layouts.

Communication Framework

The communication framework of the robotic system was based on USB-UART serial communication between the Jetson TX2 processing unit and the ATmega328 microcontroller. The Jetson TX2 processed machine learning outputs, object detection information, and autonomous navigation commands before transmitting movement instructions to the microcontroller. The ATmega328 executed commands related to forward movement, directional control, motor speed regulation, and obstacle handling. Continuous bidirectional communication enabled synchronization between sensing systems, AI processing modules, and movement control operations. The UART communication framework provided stable and low-latency data transmission necessary for real-time autonomous robotic operation within warehouse environments. This communication architecture improved operational reliability and enabled efficient coordination between hardware components and machine learning systems.

Experimental Setup

The experimental setup was designed to evaluate the performance of the AI-powered smart serving robot within simulated warehouse operational conditions. The robotic system was tested in environments containing predefined warehouse pathways, movable obstacles, and material transportation tasks to simulate realistic warehouse logistics operations. Testing scenarios included autonomous movement between storage points, obstacle avoidance during transportation, object detection under varying environmental conditions, and dynamic path recalculation during navigation. The experimental environment also incorporated moving obstacles and changing operational layouts to assess robotic adaptability and navigation stability. Warehouse simulation testing enabled comprehensive evaluation of autonomous delivery performance, route optimization capability, and real-time operational reliability within smart logistics environments.

Performance Evaluation Metrics

The performance of the robotic system was evaluated using multiple operational and technical metrics related to object detection, navigation efficiency, obstacle avoidance, and processing performance. Detection accuracy was measured to evaluate the effectiveness of the YOLOv4 object recognition framework in identifying operational targets and environmental obstacles. Navigation efficiency was assessed based on path optimization, route completion time, and autonomous movement stability during warehouse transportation tasks. Obstacle avoidance performance was evaluated through collision prevention capability and real-time path recalculation effectiveness in dynamic environments. Processing speed was measured using real-time inference performance and system response latency during autonomous operation. These evaluation metrics enabled comprehensive analysis of the effectiveness of AI-powered smart serving robots in optimizing warehouse supply chain operations and improving autonomous logistics performance.

Results

The implementation of the AI-powered smart serving robotic system demonstrated effective operational performance in optimizing warehouse supply chain activities through autonomous navigation, object detection, and intelligent delivery coordination. The integration of the YOLOv4 object detection framework with embedded machine learning processing enabled the robot to identify operational objects, warehouse pathways, and surrounding obstacles in real time. During experimental testing, the robot successfully recognized target objects and environmental boundaries using the integrated camera and convolutional neural network-based object detection system. The YOLOv4 model provided stable and accurate object localization through bounding box prediction, enabling continuous environmental perception during robotic movement. Real-time object recognition improved warehouse operational coordination by allowing the robot to autonomously identify transportation pathways and avoid interruptions during delivery operations. The deployment of the machine learning model on the Jetson TX2 platform also enabled fast inference speed and low-latency processing, which supported efficient robotic response during dynamic warehouse operations. The AI-driven perception system significantly enhanced the robot's ability to operate autonomously within warehouse environments containing varying object arrangements and movement conditions.

The autonomous navigation system implemented using the RRT* path planning algorithm demonstrated reliable path optimization and collision-free robotic movement throughout warehouse simulation testing. The robot successfully generated efficient movement trajectories between predefined operational locations while continuously adapting to changing environmental conditions. The navigation framework utilized random node sampling, nearest-neighbor expansion, and path rewiring techniques to optimize robotic movement and reduce unnecessary travel distance. During testing, the robot efficiently navigated through warehouse pathways while maintaining stable directional control and operational continuity. The integration of real-time path recalculation allowed the robot to modify movement trajectories whenever obstacles were detected within operational pathways. The

navigation algorithm also improved overall movement efficiency by selecting optimized delivery routes and minimizing delays associated with environmental obstructions. The RRT* framework demonstrated strong adaptability in warehouse environments containing dynamic obstacles and changing operational layouts, indicating the effectiveness of intelligent path planning systems for autonomous warehouse logistics applications.

The obstacle avoidance mechanism integrated within the robotic system significantly improved operational safety and navigation reliability during autonomous movement. Ultrasonic sensors continuously monitored surrounding environmental conditions and successfully detected nearby objects positioned within predefined threshold distances. When obstacles were identified during movement, the robotic system automatically suspended forward navigation and recalculated alternative trajectories to prevent collisions. The combination of ultrasonic sensing and AI-based environmental perception enabled the robot to respond effectively to both stationary and moving obstacles within simulated warehouse conditions. Experimental observations showed that the robot maintained stable obstacle avoidance performance even within crowded operational spaces containing temporary barriers and dynamic environmental changes. The sensor fusion approach integrating distance sensing and computer vision enhanced environmental awareness and reduced navigation uncertainty during warehouse transportation tasks. The obstacle avoidance framework therefore contributed significantly to improving robotic operational stability, autonomous adaptability, and delivery safety within dynamic warehouse logistics environments.

The robotic system also demonstrated efficient warehouse transportation performance during material handling and autonomous delivery operations. The robot successfully transported operational loads between predefined locations while maintaining stable movement control and navigation accuracy. The integration of intelligent path planning and autonomous navigation improved transportation efficiency by reducing delivery time and minimizing unnecessary movement. Real-time object detection further enhanced transportation reliability by enabling the robot to identify operational targets and navigate efficiently within warehouse pathways. The automated transportation mechanism reduced the need for manual material handling and supported continuous logistics operations without significant interruptions. During repeated operational cycles, the robotic system maintained stable delivery coordination and movement precision, indicating strong potential for warehouse automation applications involving inventory movement and internal logistics management. The autonomous delivery capability also improved operational productivity by enabling efficient transportation within simulated warehouse environments representative of real-world supply chain operations.

The communication framework based on USB-UART serial communication between the Jetson TX2 and ATmega328 microcontroller demonstrated stable and reliable system coordination throughout experimental evaluation. The communication architecture enabled continuous bidirectional data transfer between machine learning processing modules, sensing systems, and motor control operations. Navigation commands generated through the AI processing system were accurately transmitted to the microcontroller for movement execution, enabling smooth forward movement, directional control, and obstacle handling during autonomous operation. The

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>

communication system maintained low-latency performance and stable synchronization throughout repeated operational cycles, improving overall robotic responsiveness and control reliability. Real-time communication also enabled continuous environmental monitoring and rapid decision-making during warehouse navigation tasks. The integration of machine learning processing with embedded communication systems therefore enhanced operational coordination and supported stable autonomous warehouse logistics performance.

Overall experimental evaluation demonstrated that the AI-powered smart serving robotic system achieved reliable autonomous operational performance within warehouse supply chain environments. The integration of machine learning algorithms, autonomous navigation frameworks, sensor fusion technologies, and embedded communication systems enabled the robot to perform intelligent warehouse transportation tasks with minimal human intervention. The object detection framework achieved stable recognition accuracy and environmental perception, while the RRT* navigation system provided efficient path optimization and collision-free movement. Obstacle avoidance mechanisms improved operational safety and navigation adaptability in dynamic environments, and the communication architecture supported stable system coordination and low-latency movement control. The robotic system successfully optimized warehouse transportation operations by reducing delivery delays, improving route efficiency, and supporting continuous logistics coordination. The findings indicate that AI-powered smart serving robots have substantial potential to enhance warehouse automation, supply chain productivity, and intelligent logistics operations within Industry 4.0 environments.

Table 1. Overall Performance Evaluation of AI-Powered Smart Serving Robot

Performance Parameter	Result
Object Detection Accuracy	92%
Real-Time Processing Speed	28 FPS
Navigation Efficiency	High
Obstacle Avoidance Success Rate	95%
Collision-Free Navigation	Successful
Delivery Coordination	Stable
Communication Latency	Minimal
Autonomous Transportation	Effective
Route Optimization	Improved
Operational Reliability	Stable




Figure 3 YOLOv4-based object detection framework for real-time warehouse object recognition and intelligent robotic perception.

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>




Figure 4 RRT-based autonomous navigation and smart serving robot prototype for optimized warehouse supply chain operations.

Discussion

The integration of artificial intelligence within warehouse logistics operations has significantly transformed the efficiency and intelligence of modern supply chain systems. The findings of this study demonstrate that AI-powered smart serving robots can substantially improve autonomous warehouse operations through real-time object detection, intelligent navigation, obstacle avoidance, and automated material transportation. The implementation of machine learning algorithms, particularly YOLOv4 and convolutional neural networks, enabled the robotic system to achieve accurate environmental perception and operational awareness within dynamic warehouse environments. Artificial intelligence improved the robot's ability to recognize objects, identify operational pathways, and make autonomous decisions without continuous human supervision. The integration of AI with embedded robotic systems also enhanced operational adaptability, enabling the robot to respond to changing warehouse conditions and environmental uncertainties in real time. These findings confirm that machine learning technologies can effectively support intelligent logistics automation by improving robotic responsiveness, route optimization, and operational coordination within warehouse supply chain systems. The application of AI-driven autonomous systems therefore represents a significant advancement in Industry 4.0 warehouse management and smart logistics infrastructure[34], [35], [36], [37], [38], [39], [40], [41].

The autonomous navigation framework implemented using the RRT* path planning algorithm demonstrated strong effectiveness in improving movement efficiency and reducing navigation complexity within warehouse environments. The robotic system successfully generated optimized collision-free trajectories and continuously adapted movement paths according to environmental changes and obstacle conditions. The integration of intelligent path planning significantly reduced unnecessary movement and enabled the robot to maintain efficient transportation performance during operational tasks. Real-time path recalculation further enhanced navigation reliability by allowing the robot to dynamically modify movement trajectories whenever obstacles or pathway interruptions were detected. The navigation system also demonstrated strong stability during repeated operational cycles, indicating that AI-based path planning approaches are highly suitable for autonomous warehouse logistics applications. The use of smart navigation technologies can therefore reduce operational delays, improve route optimization, and support continuous warehouse transportation activities with minimal human intervention. These results highlight the importance of intelligent navigation frameworks in enabling autonomous warehouse robotics to operate efficiently within complex and dynamic supply chain environments[42], [43], [44], [45], [46].

The implementation of AI-powered smart serving robots also demonstrated substantial improvements in warehouse productivity and logistics coordination. Autonomous robotic transportation reduced dependency on manual material handling and enabled continuous operational workflows without fatigue-related interruptions or human-based inconsistencies. The robotic system successfully optimized transportation efficiency by reducing delivery delays, improving movement precision, and supporting real-time logistics coordination within warehouse pathways. Intelligent object detection and autonomous navigation further enhanced warehouse

productivity by minimizing operational errors and improving delivery accuracy during inventory transportation tasks. The ability of the robotic system to operate continuously and autonomously provides significant advantages for modern warehouse environments that require high-speed logistics coordination and uninterrupted operational performance. Additionally, the implementation of autonomous robots can reduce workforce pressure and improve overall supply chain reliability by automating repetitive transportation tasks traditionally performed by human workers. These findings demonstrate that AI-powered warehouse robotics can significantly contribute to operational productivity, smart logistics optimization, and warehouse automation efficiency within Industry 4.0 infrastructure systems[47], [48], [49], [50].

Compared with traditional warehouse management systems, the AI-powered robotic framework developed in this study provided several operational and technological advantages. Conventional warehouse logistics operations primarily depend on manual labor, fixed transportation infrastructure, and human-based inventory coordination, which often result in increased operational costs, slower transportation speed, and higher error rates. In contrast, the autonomous robotic system implemented in this study demonstrated improved route optimization, intelligent environmental interaction, and adaptive operational decision-making. The integration of machine learning algorithms enabled the robot to autonomously recognize operational targets, avoid obstacles, and navigate efficiently without requiring fixed pathways or continuous human supervision. Traditional warehouse systems also face limitations related to workforce fatigue, inconsistent productivity, and restricted operational flexibility, whereas autonomous robotic systems can maintain stable performance and continuous logistics coordination over extended operational periods. Furthermore, AI-driven navigation systems provide greater adaptability in dynamic warehouse environments where operational layouts and transportation conditions frequently change. These comparative advantages indicate that AI-powered smart serving robots have the potential to replace or significantly enhance conventional warehouse transportation systems through intelligent automation and autonomous logistics optimization[51], [52], [53], [54], [55], [56], [57], [58], [59].

Despite the strong operational performance demonstrated during experimental evaluation, several challenges and limitations associated with AI-powered warehouse robotics remain evident. One of the primary limitations involves computational constraints associated with real-time machine learning processing on embedded robotic systems. High-performance object detection algorithms and autonomous navigation frameworks require significant computational resources, which may create latency issues and reduce operational responsiveness in resource-constrained robotic platforms. Dynamic warehouse environments also present substantial navigation challenges due to the presence of moving obstacles, temporary barriers, and continuously changing operational layouts. Although the implemented obstacle avoidance system successfully prevented collisions during testing, highly crowded warehouse conditions may still affect navigation precision and route optimization performance. Sensor inaccuracies and environmental noise can further reduce the reliability of environmental perception and obstacle detection systems, particularly in low-visibility operational conditions. Battery limitations and energy consumption

associated with continuous robotic operation also remain significant challenges for long-term warehouse deployment. Additionally, communication delays and synchronization issues between embedded processing systems and motor control frameworks may impact autonomous coordination during complex operational tasks. These limitations highlight the need for more advanced machine learning optimization, lightweight processing architectures, and improved sensor integration for future warehouse robotic systems[60], [61], [62], [63], [64].

Future improvements in AI-powered warehouse robotics should focus on enhancing autonomous intelligence, operational scalability, and real-time decision-making capabilities. The implementation of more advanced deep learning architectures and lightweight object detection models could significantly improve processing efficiency while reducing computational overhead within embedded robotic systems. Reinforcement learning techniques may further enhance robotic adaptability by enabling autonomous learning from environmental interaction and operational experience. Future warehouse robots should also incorporate advanced sensor fusion technologies integrating LiDAR, depth cameras, inertial measurement units, and multiple environmental sensing systems to improve navigation reliability and obstacle detection accuracy. The integration of cloud-edge computing frameworks could further optimize robotic operational coordination by enabling distributed data processing and real-time warehouse monitoring across multiple robotic units. Energy-efficient hardware architectures and intelligent battery management systems are also essential for improving long-term operational sustainability and reducing maintenance requirements within warehouse environments. Additionally, future research should focus on large-scale real-world implementation of AI-powered warehouse robotics to evaluate operational reliability, scalability, and economic feasibility within industrial logistics systems. The continued advancement of artificial intelligence, autonomous navigation, and embedded robotics technologies is expected to significantly accelerate the development of intelligent warehouse automation systems capable of transforming future supply chain operations and smart logistics infrastructure[65], [66], [67], [68], [69], [70], [71], [72], [73], [74], [75], [76], [77], [78], [79], [80], [81], [82], [83], [84].

Conceptual framework

The conceptual framework of this study is based on the integration of artificial intelligence algorithms, embedded sensor technologies, autonomous navigation systems, and warehouse operational processes to optimize supply chain efficiency through AI-powered smart serving robots. The framework identifies AI algorithms such as YOLOv4 object detection, convolutional neural networks, and RRT* path planning as the primary independent variables responsible for improving robotic intelligence, environmental perception, and autonomous decision-making. These machine learning models are integrated with embedded sensing components including cameras, ultrasonic sensors, and microcontroller-based communication systems to enhance real-time object recognition, obstacle detection, and navigation accuracy within warehouse environments. Autonomous navigation systems act as mediating variables that support intelligent movement, collision-free transportation, route optimization, and adaptive robotic coordination during warehouse operations. The interaction between AI processing and sensor-based environmental perception enables

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>

the robotic system to autonomously identify operational pathways, avoid dynamic obstacles, and execute delivery tasks with minimal human intervention. The dependent variables within the framework include operational efficiency, transportation speed, workload reduction, warehouse productivity, and supply chain optimization. The framework assumes that the effective integration of machine learning, sensor fusion, and intelligent navigation systems significantly improves autonomous warehouse logistics performance. Consequently, the implementation of AI-powered smart serving robots results in faster delivery operations, reduced manual workload, enhanced transportation reliability, and optimized warehouse supply chain coordination within Industry 4.0 operational environments.




Figure 5 Conceptual framework illustrating AI algorithms, autonomous navigation, and operational efficiency for warehouse supply chain optimization using smart serving robots.

Conclusion

The study demonstrated that AI-powered smart serving robots significantly improve warehouse supply chain operations through intelligent automation, autonomous navigation, and real-time logistics coordination. The integration of YOLOv4 object detection, convolutional neural networks, RRT* path planning, sensor fusion, and embedded communication systems enabled the robotic platform to perform autonomous warehouse transportation tasks with high operational reliability and

minimal human intervention. Experimental findings confirmed that the robotic system achieved stable object recognition, efficient obstacle avoidance, optimized navigation performance, and reliable communication coordination within simulated warehouse environments. The implementation of intelligent robotic systems reduced delivery delays, improved transportation efficiency, minimized manual operational workload, and enhanced overall warehouse productivity. The study also highlighted the importance of machine learning and autonomous navigation technologies in supporting Industry 4.0 warehouse automation and smart logistics infrastructure. Although limitations related to computational constraints, energy consumption, and dynamic environmental complexity remain significant challenges, the developed system demonstrated strong potential for future autonomous warehouse applications. The study concludes that AI-powered smart serving robots represent a transformative solution for optimizing warehouse logistics, improving operational efficiency, and enabling intelligent supply chain management within modern industrial environments.

Recommendation

The study recommends the implementation of lightweight and high-performance machine learning models to improve the real-time operational efficiency of AI-powered warehouse robots. Future robotic systems should integrate advanced sensor fusion technologies combining cameras, ultrasonic sensors, LiDAR, and inertial measurement units to enhance obstacle detection accuracy and autonomous navigation reliability within dynamic warehouse environments. Warehouse operators are encouraged to adopt autonomous robotic transportation systems to reduce manual workload, improve delivery coordination, and optimize inventory movement within supply chain operations. The study further recommends the use of cloud-edge computing integration to support real-time warehouse monitoring, distributed robotic coordination, and intelligent logistics management. Future robotic systems should also incorporate reinforcement learning algorithms to improve adaptive navigation and autonomous decision-making through continuous environmental learning. Additionally, energy-efficient embedded hardware architectures and intelligent battery management systems should be developed to improve long-term robotic operational sustainability. Large-scale real-world deployment and testing within industrial warehouse environments are also necessary to evaluate operational scalability, economic feasibility, and long-term performance reliability of AI-powered smart serving robots within modern supply chain infrastructure.

References

- [1] L. Sousa *et al.*, "Obstacle Avoidance Technique for Mobile Robots at Autonomous Human-Robot Collaborative Warehouse Environments," *Sensors (Basel)*, vol. 25, 2025, doi: 10.3390/s25082387.
- [2] S. Zhang, "A Design of Obstacle Avoidance and Grabbing Manipulator Based on Computer Vision for Warehouse Inspection Robot," *Highlights Sci. Eng. Technol.*, 2023, doi: 10.54097/hset.v52i.8886.
- [3] A. A. R, P. P. A, N. G. N. G. M, and V. R. V. R. P, "AI-Driven Autonomous Mobile Robot with Vision-Based SLAM for Intelligent Warehouse Navigation," *Int. J. Creat. Open Res. Eng. Manag.*, 2026, doi: 10.55041/ijcope.v2i4.344.

- [4] H.-Y. Lin, K.-L. Chang, and H.-Y. Huang, "Development of Unmanned Aerial Vehicle Navigation and Warehouse Inventory System Based on Reinforcement Learning," *Drones*, 2024, doi: 10.3390/drones8060220.
- [5] D. Sayfullaev, Z. A. Balsem, A. A. Majeed, A. A. Gulomjonugli, and G. B. Shivaji, "Autonomous Logistics: The Role of Artificial Intelligence, Drones, And Robotics In Supply Chain Management," in *2025 International Conference on Computational Innovations and Engineering Sustainability (ICCIES)*, 2025, pp. 1–6. doi: 10.1109/iccies63851.2025.11032336.
- [6] X. Liu, G. Gong, X. Hu, G. Shang, and H. Zhu, "Cognitive Enhancement of Robot Path Planning and Environmental Perception Based on Gmapping Algorithm Optimization," *Electronics*, 2024, doi: 10.3390/electronics13050818.
- [7] C. K. M. Lee, B. Lin, K. Ng, Y. Lv, and W. Tai, "Smart robotic mobile fulfillment system with dynamic conflict-free strategies considering cyber-physical integration," *Adv. Eng. Informatics*, vol. 42, 2019, doi: 10.1016/j.aei.2019.100998.
- [8] M.-K. Ng, Y.-W. Chong, K. Ko, Y. Park, and Y. Leau, "Adaptive path finding algorithm in dynamic environment for warehouse robot," *Neural Comput. Appl.*, vol. 32, pp. 13155–13171, 2020, doi: 10.1007/s00521-020-04764-3.
- [9] T.-T. Banh, X.-T. Nguyen, T. Le, T.-B. Tran, and B.-T. Vuong, "Efficient Algorithms on Dynamic Obstacle Avoidance for Multi-Robot Agents In Automated Warehouse System," in *Proceedings of the 2024 9th International Conference on Intelligent Information Technology*, 2024. doi: 10.1145/3654522.3654593.
- [10] K. Li *et al.*, "Deep Reinforcement Learning-based Obstacle Avoidance for Robot Movement in Warehouse Environments," in *2024 IEEE 6th International Conference on Civil Aviation Safety and Information Technology (ICCASIT)*, 2024, pp. 342–348. doi: 10.1109/iccasit62299.2024.10828100.
- [11] A. A. Adil, S. Sakhrich, J. Mounsef, and N. Maalouf, "A multi-robot collaborative manipulation framework for dynamic and obstacle-dense environments: integration of deep learning for real-time task execution," *Front. Robot. AI*, vol. 12, 2025, doi: 10.3389/frobt.2025.1585544.
- [12] O. Akanbi and E. A. Sunday, "A Systematic Review of AI-Driven Autonomous Mobile Robots (AMR) in Scalable Micro-Fulfillment Centers," *Int. J. Adv. Multidiscip. Res. Stud.*, 2025, doi: 10.62225/2583049x.2025.5.6.6182.
- [13] G. B, D. B, and D. J, "AUTONOMOUS WITH GPS BASED CONTROLLED MOBILE ROBOT FOR MATERIAL HANDLING IN WAREHOUSE," *J. Dyn. Control*, 2025, doi: 10.71058/jodac.v9i3004.
- [14] S. Li, "Dynamic Path Planning and Obstacle Avoidance for Mobile Robots via Machine Vision," in *ITM Web of Conferences*, 2026. doi: 10.1051/itmconf/20268404028.
- [15] C. Elfathi, L. Laaouina, A. Jeghal, and H. Tairi, "Intelligent Agents in Smart Logistics and Warehouse Automation: Overview," in *2025 5th International Conference on Innovative Research in Applied Science, Engineering and Technology (IRASET)*, 2025, pp. 1–8. doi:

- 10.1109/iraset64571.2025.11008349.
- [16] K. Li *et al.*, “Research on Reinforcement Learning Based Warehouse Robot Navigation Algorithm in Complex Warehouse Layout,” in *2024 6th International Conference on Artificial Intelligence and Computer Applications (ICAICA)*, 2024, pp. 296–301. doi: 10.1109/icaica63239.2024.10823054.
- [17] J. Martínez, L. Timaná, and C. Suárez, “Application of a Computer Vision Algorithm for Robot Motion Planning and Obstacle Avoidance,” *2023 Congr. Int. Innovación y Tendencias en Ing.*, pp. 1–6, 2023, doi: 10.1109/coniiti61170.2023.10324018.
- [18] T. Raamets, J. Maják, K. Karjust, K. Mahmood, and A. Hermaste, “Autonomous mobile robots for production logistics: a process optimization model modification,” *Proc. Est. Acad. Sci.*, 2024, doi: 10.3176/proc.2024.2.06.
- [19] S. D. C. S. Araujo *et al.*, “ResNet-18 based multi-task visual inference and adaptive control for an edge-deployed autonomous robot,” *Front. Robot. AI*, vol. 12, 2025, doi: 10.3389/frobt.2025.1680285.
- [20] V. K. Prajapati, S. A. Shashank, and M. Nithya, “Computer Vision Enabled Pick and Place Robot for Warehouse Automation,” in *2024 5th International Conference on Smart Electronics and Communication (ICOSEC)*, 2024, pp. 641–646. doi: 10.1109/icosec61587.2024.10722718.
- [21] Z. Khalid and H. H. Raza, “AI-POWERED AUTOMATION IN LOGISTICS AND WAREHOUSING,” *Int. J. Comput. Biol. Sci.*, 2025, doi: 10.66238/ijcbs17.
- [22] H. Ren, “Path Avoidance System of Intelligent Robot Based on Computer Vision,” in *Journal of Physics: Conference Series*, 2023. doi: 10.1088/1742-6596/2493/1/012016.
- [23] B. Kim, Y. Kim, and S. Lee, “Decentralised protocols for autonomous mobile robots in material handling: inductive learnings from centralised controller,” *Int. J. Prod. Res.*, vol. 63, pp. 1372–1398, 2024, doi: 10.1080/00207543.2024.2376213.
- [24] K. Zhang, “OBSTACLE AVOIDANCE PATH OF WHEELED AGRICULTURAL HANDLING ROBOTS IN WAREHOUSE BASED ON IMPROVED ACO-DWA ALGORITHM,” *INMATEH Agric. Eng.*, 2024, doi: 10.35633/inmateh-74-51.
- [25] K. Kumar, V. P. N. G. M. P. A., and A. R., “AI-Augmented SLAM for Warehouse Robots,” *Int. J. Creat. Open Res. Eng. Manag.*, 2026, doi: 10.55041/ijcope.v2i4.621.
- [26] C. Patruno, V. Renó, M. Nitti, N. Mosca, M. Di Summa, and E. Stella, “Vision-based omnidirectional indoor robots for autonomous navigation and localization in manufacturing industry,” *Heliyon*, vol. 10, 2024, doi: 10.1016/j.heliyon.2024.e26042.
- [27] J. Zhou and R. Lu, “Image Recognition Technology Applied to the Design of Mobile Platform for Warehouse Logistics Robots,” *Appl. Math. Nonlinear Sci.*, vol. 9, 2023, doi: 10.2478/amns.2023.2.01714.
- [28] V. P. Prabu, “Improving Warehouse Automation Using Artificial Intelligence and Robotics,” *Int. J. Sci. Technol.*, 2022, doi: 10.71097/ijtsat.v13.i1.3380.

- [29] P. Pikulin, V. Lishunov, and K. Kułakowski, "Optimizing Path Planning for Automated Guided Vehicles in Constrained Warehouse Environments: Addressing the Challenges of Non-Rotary Platforms and Irregular Layouts," *Robotics*, vol. 14, p. 39, 2025, doi: 10.3390/robotics14040039.
- [30] H. Wang, "Multimodal audio-visual robot fusing 3D CNN and CRNN for player behavior recognition and prediction in basketball matches," *Front. Neurorobot.*, vol. 18, 2024, doi: 10.3389/fnbot.2024.1284175.
- [31] X. Hu, "Artificial Intelligence and Internet of Things Logistics Optimization: Research on Logistics Robot-Based Optimization A Case Study of the Amazon Model," *Adv. Econ. Manag. Polit. Sci.*, 2026, doi: 10.54254/2754-1169/2026.ld31913.
- [32] O. B. Alhas, M. Oruc, G. B. Usta, H. Marah, B. T. Tezel, and M. Challenger, "Towards developing a cyber-physical warehouse system for automated order-picking for online shopping," pp. 321–328, 2022, doi: 10.15439/2022f208.
- [33] S. R. Vuyyuru, "Intelligent Automation Revolutionizing Retail Operations by Optimizing Inventory Management, Logistics, and Customer Service with AI-Powered Robotics and Machine Learning," *Int. J. Innov. Res. Eng. & Multidiscip. Phys. Sci.*, 2025, doi: 10.37082/ijirms.v13.i2.232405.
- [34] X. Fan and Z. Gu, "Obstacle Avoidance Path Optimization of Agricultural Warehouse Handling Robots Based on the Stanley-PPO2 Algorithm," *J. Eng. Sci. Technol. Rev.*, 2025, doi: 10.25103/jestr.183.16.
- [35] A. Abdi, M. Ranjbar, and J. H. Park, "Computer Vision-Based Path Planning for Robot Arms in Three-Dimensional Workspaces Using Q-Learning and Neural Networks," *Sensors (Basel)*, vol. 22, 2022, doi: 10.3390/s22051697.
- [36] R. Rainer, R. Richey, and S. Chowdhury, "How Robotics is Shaping Digital Logistics and Supply Chain Management: An Ongoing Call for Research," *J. Bus. Logist.*, 2025, doi: 10.1111/jbl.70005.
- [37] Y. Liu, H. Wang, and D. Jia, "Human Following Based on Visual Perception in the Context of Warehouse Logistics," *ArXiv*, vol. abs/2301.02978, 2023, doi: 10.48550/arxiv.2301.02978.
- [38] C. Devi, K. Balasubramanian, and N. Rajeswari, "AI-Powered Supply Chain Management in Manufacturing: A Data-Driven Approach to Materials Logistics," in *2025 IEEE 6th International Conference in Robotics and Manufacturing Automation (ROMA)*, 2025, pp. 135–140. doi: 10.1109/roma66616.2025.11155325.
- [39] A. Shahzad, X. Gao, A. Yasin, K. Javed, and S. Anwar, "A Vision-Based Path Planning and Object Tracking Framework for 6-DOF Robotic Manipulator," *IEEE Access*, vol. 8, pp. 203158–203167, 2020, doi: 10.1109/access.2020.3037540.
- [40] Z. Wei, F. Tian, Z. Qiu, Z. Yang, R. Zhan, and J. Zhan, "Research on Machine Vision-Based Control System for Cold Storage Warehouse Robots," *Actuators*, 2023, doi: 10.3390/act12080334.
- [41] S. Parikh1, "The Future of E-Commerce Fulfillment: Harnessing Advanced Robotics and System Optimization in U.S. Retail," *INTERANTIONAL J. Sci. Res. Eng. Manag.*, 2025, doi: 10.55041/ijrsrem41597.
- [42] P. Wu, L. Zhong, J. Xiong, Y. Zeng, and M. Pei, "Two-level vehicle path

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>

- planning model for multi-warehouse robots with conflict solution strategies and improved ACO,” *J. Intell. Connect. Veh.*, 2023, doi: 10.26599/jicv.2023.9210011.
- [43] T. M., R. P., S. K., D. Maurya, M. K., and S. E., “AI-Powered Autonomous Robots for Large-Scale Warehouse Cleaning and Maintenance with IoT Integration,” in *2025 11th International Conference on Communication and Signal Processing (ICCSP)*, 2025, pp. 497–501. doi: 10.1109/iccsp64183.2025.11088692.
- [44] Shoeib M., J. Lewandowski, and A. Omara, “A novel methodology for vision-based path planning and obstacle avoidance in mobile robot applications,” *Adv. Robot.*, vol. 38, pp. 802–817, 2024, doi: 10.1080/01691864.2024.2315591.
- [45] V. Manwatkar, “Autonomous Logistics Networks for E-Commerce Fulfillment: Scalable AI and Robotics Integration,” *Eur. Mod. Stud. J.*, 2025, doi: 10.59573/emsj.9(4).2025.87.
- [46] S. Kodadi, D. Deevi, N. Allur, K. Dondapati, H. Chetlapalli, and T. M., “AI-Optimized Warehouse Systems: Combining AGVs, RFID Technology, Zigbee Networks, and Agent-based Simulation Models,” in *2025 6th International Conference on Intelligent Communication Technologies and Virtual Mobile Networks (ICICV)*, 2025, pp. 1811–1817. doi: 10.1109/icicv64824.2025.11085852.
- [47] H. Mahajan *et al.*, “Automatic robot Manoeuvres detection using computer vision and deep learning techniques: a perspective of internet of robotics things (IoRT),” *Multimed. Tools Appl.*, vol. 82, pp. 23251–23276, 2022, doi: 10.1007/s11042-022-14253-5.
- [48] A. Kochnev, “HOW AUTONOMOUS ROBOTS AND INDOOR MAPPING IMPROVE WAREHOUSE SAFETY,” in *SGEM International Multidisciplinary Scientific GeoConference EXPO Proceedings*, 2025. doi: 10.5593/sgem2025/2.1/s10.25.
- [49] Z. Wang, H. Xu, and Y. Wan, “Wheeled Robots Path Planing and Tracking System Based on Monocular Visual SLAM,” *ArXiv*, vol. abs/1807.06303, 2018, [Online]. Available: <https://consensus.app/papers/wheeled-robots-path-planing-and-tracking-system-based-on-wang-xu/57184397a2ea56c292609a349d0e2658/>
- [50] K. C. Yarlagadda, “AI-Powered Supply Chain Optimization: Enhancing Demand Forecasting and Logistics,” *J. Comput. Sci. Technol. Stud.*, 2025, doi: 10.32996/jcsts.2025.7.4.92.
- [51] Y. Shou, “Obstacle Avoidance Path Planning Algorithm of an Embedded Robot Based on Machine Vision,” *Mob. Inf. Syst.*, 2022, doi: 10.1155/2022/3068614.
- [52] O. M. Banur, B. Patle, and S. Pawar, “Integration of robotics and automation in supply chain: a comprehensive review,” *Robot. Syst. Appl.*, 2024, doi: 10.21595/ras.2023.23349.
- [53] K. Sugimoto, S. Ishihara, and M. Itoh, “Mobile Robot Navigation in Warehouses by MPC Handling Multiple Travel Strategies Considering Independent Safety LiDAR,” *2024 IEEE/SICE Int. Symp. Syst. Integr.*, pp.

- 1085–1092, 2024, doi: 10.1109/sii58957.2024.10417666.
- [54] M. Shamsuddoha, E. Khan, M. Chowdhury, and T. Nasir, “Revolutionizing Supply Chains: Unleashing the Power of AI-Driven Intelligent Automation and Real-Time Information Flow,” *Inf.*, vol. 16, p. 26, 2025, doi: 10.3390/info16010026.
- [55] C. Scoccia, B. Ubezio, G. Palmieri, M. Rathmair, and M. Hofbaur, “Experimental Assessment of a Vision-Based Obstacle Avoidance Strategy for Robot Manipulators: Off-line Trajectory Planning and On-line Motion Control,” *J. Intell. Robot. Syst.*, vol. 110, 2024, doi: 10.1007/s10846-024-02146-8.
- [56] K. Paul, L. Nafees, A. Hazra, and S. Ghosh, “AI-Driven Industrial Robotics: Revolutionizing Automation with Machine Learning and Intelligent Adaptation,” *Int. J. Multidiscip. Res.*, 2025, doi: 10.36948/ijfmr.2025.v07i01.37805.
- [57] R. Mulla., B. Jadhav, R. Nadaf, and H. Gaikwad, “A Novel Approach For Collision Avoidance In Collaborative Robotics Application,” *Metall. Mater. Eng.*, 2025, doi: 10.63278/1656.
- [58] D. Yaraddi, D. Murthy, and R. Navalagi, “Transforming Supply Chain Management with Next-Generation Technology (AI, Drones and Robots)- A Bibliographic Review,” *J. Inf. Syst. Eng. Manag.*, 2025, doi: 10.52783/jisem.v10i38s.7021.
- [59] V. Patil, K. Dighe, B. Landage, and V. Bhope, “Automated Robot for Warehouse using Image Processing,” *Int. J. Eng. Res. Technol.*, vol. 5, 2016, doi: 10.17577/ijertv5is030670.
- [60] S. Sanjay and S. S. Beldar, “AI and robotics in cold chain logistics: Overcoming the barriers to full automation,” *World J. Adv. Eng. Technol. Sci.*, 2025, doi: 10.30574/wjaets.2025.15.3.1005.
- [61] M. Taha and Q. M. Qadir, “Cost Effective and Easily Configurable Indoor Navigation System,” *UKH J. Sci. Eng.*, 2021, doi: 10.25079/ukhjse.v5n1y2021.pp60-72.
- [62] “Deep Learning-based mobile robot for warehouse keeping,” 2019. doi: 10.35940/ijeat.a1108.1291s419.
- [63] M. Helgo, “Development and Evaluation of a Computer Vision System for Robot Navigation and Object Recognition in Real-World Environments,” *J. Comput. Nat. Sci.*, 2024, doi: 10.53759/181x/jcns202404007.
- [64] W. Małopolski and S. Skoczypiec, “The Concept of an Autonomous Mobile Robot for Automating Transport Tasks in High-Bay Warehouses,” *Adv. Sci. Technol. Res. J.*, 2024, doi: 10.12913/22998624/182932.
- [65] L. Yang and W. Lei, “Computer Vision Positioning and Local Obstacle Avoidance Optimization Based on Neural Network Algorithm,” *Comput. Intell. Neurosci.*, vol. 2022, 2022, doi: 10.1155/2022/3061910.
- [66] Z. Li, “Review of Application of AI in Amazon Warehouse Management,” *Adv. Econ. Manag. Polit. Sci.*, 2024, doi: 10.54254/2754-1169/2024.ga18980.
- [67] N. Adiuku, N. Avdelidis, G. Tang, and A. Plastropoulos, “Improved Hybrid Model for Obstacle Detection and Avoidance in Robot Operating System Framework (Rapidly Exploring Random Tree and Dynamic Windows

- Approach),” *Sensors (Basel)*, vol. 24, 2024, doi: 10.3390/s24072262.
- [68] P. Li, “Machinery and logistics: Development trends and prospects of automated warehouse technology,” *Appl. Comput. Eng.*, 2024, doi: 10.54254/2755-2721/65/20240472.
- [69] Y. Zheng, B. Yan, Chao, X. Wang, and H. Xue, “Research on obstacle detection and path planning based on visual navigation for mobile robot,” in *Journal of Physics: Conference Series*, 2020. doi: 10.1088/1742-6596/1601/6/062044.
- [70] Y.-W. Chen, J.-H. Guo, and K. Hsia, “Research on dynamic obstacle avoidance and complex path planning strategies based on ROS robots,” in *Proceedings of International Conference on Artificial Life and Robotics*, 2024. doi: 10.5954/icarob.2024.os5-1.
- [71] M. Mrad, M. Frikha, and Y. Boujelbène, “A Comprehensive Survey of Artificial Intelligence and Robotics for Reducing Carbon Emissions in Supply Chain Management,” *Logistics*, 2025, doi: 10.3390/logistics9030104.
- [72] N. Adiuku, N. Avdelidis, G. Tang, A. Plastropoulos, and Y. Diallo, “Mobile Robot Obstacle Detection and Avoidance with NAV-YOLO,” *Int. J. Mech. Eng. Robot. Res.*, 2024, doi: 10.18178/ijmerr.13.2.219-226.
- [73] T. O. Adesoga, T. Olusola, K. Nwafor, U. Temitope, E. A. Ikekwere, and D. Ekwunife, “The rise of the ‘smart’ supply chain: How AI and automation are revolutionizing logistics,” *Int. J. Sci. Res. Arch.*, 2024, doi: 10.30574/ijrsra.2024.12.2.1304.
- [74] X. Du, “Research on Robot Visual Obstacle Avoidance System Based on Neural Networks,” in *2025 IEEE 5th International Conference on Electronic Technology, Communication and Information (ICETCI)*, 2025, pp. 915–919. doi: 10.1109/icetci64844.2025.11084099.
- [75] Z. Chen, T. Gu, Z. Chen, and B. Zhang, “Task Allocation Algorithm and Simulation Analysis for Multiple AMRs in Digital-Intelligent Warehouses,” *Concurr. Comput. Pract. Exp.*, vol. 37, 2025, doi: 10.1002/cpe.8382.
- [76] L. Duan, “Path Planning for Batch Picking of Warehousing and Logistics Robots Based on Modified A* Algorithm,” *Int. J. Online Eng.*, vol. 14, pp. 176–192, 2018, doi: 10.3991/ijoe.v14i11.9527.
- [77] M. U. Mojumder and M. Nuruzzaman, “AI-Driven Optimization of Warehouse Layout and Material Handling: A Quantitative Study on Efficiency and Space Utilization,” *Rev. Appl. Sci. Technol.*, 2025, doi: 10.63125/bgxb1z53.
- [78] L. Lin, J. Guo, and L. Liu, “Multi-scene application of intelligent inspection robot based on computer vision in power plant,” *Sci. Rep.*, vol. 14, 2024, doi: 10.1038/s41598-024-56795-8.
- [79] A. K. Pinagapani, A. G. A. S. N. K. R. and P. B., “Automated material handling for inventory management system,” *Acta IMEKO*, 2024, doi: 10.21014/actaimeko.v13i4.1728.
- [80] D. Ball *et al.*, “Vision-based Obstacle Detection and Navigation for an Agricultural Robot,” *J. F. Robot.*, vol. 33, 2016, doi: 10.1002/rob.21644.
- [81] U. Periasamy, A. Senathirajah, K. Soliman, R. Haque, and T. Lertatthakornkit, “The impact of AI-powered robotics and workforce dynamics on productivity

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>

- in the logistics industry,” *Int. J. Innov. Res. Sci. Stud.*, 2025, doi: 10.53894/ijirss.v8i5.9431.
- [82] A. Timofeev and F. Daeef, “Control of a transport robot in extreme weather based on computer vision systems,” in *Journal of Physics: Conference Series*, 2021. doi: 10.1088/1742-6596/2131/3/032027.
- [83] G. Fragapane, R. Koster, F. Sgarbossa, and J. Strandhagen, “Planning and control of autonomous mobile robots for intralogistics: Literature review and research agenda,” *Eur. J. Oper. Res.*, vol. 294, pp. 405–426, 2021, doi: 10.1016/j.ejor.2021.01.019.
- [84] G. Radhakrishnan, M. Gabhane, S. Jha, N. Al Said, B. Suv, and R. Murthy, “AI and IoT in Supply Chains: Creating Intelligent and Autonomous Business Operations,” *J. Inf. Syst. Eng. Manag.*, 2025, doi: 10.52783/jisem.v10i11s.1664.