

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>

Advanced AI-Driven Architecture for Real-Time Monitoring and Intelligent Fault Detection of Aircraft Engine Compressor and Fuel Systems under Emergency Operating Conditions

Syed Kumail Abbas Zaidi (Corresponding Author)

Department of Electrical and Computer Engineering, Lamar University, Texas, United State of America. Email: kumail.800@gmail.com

Aftab Ahmed Soomro

Department of Mechanical Engineering Technology, Benazir Bhutto Shaheed University of Technology and Skill Development Khairpur Mirs, Sindh, Pakistan.

Email: aftabsoomro@bbsutsd.edu.pk

Basit Ahmad

Department of Electrical Engineering, NFC Institute of Engineering and Technology, Multan 60000, Pakistan. Email: basitahmad3884@gmail.com

Sohaib Hafeez

Department of Mechatronics Engineering, Huazhong University of Science and Technology, China. Email: sohaib.hafeez@hotmail.com

Muhammad Kashif Majeed

Faculty of Engineering Science and Technology, Iqra University, Karachi 75500, Pakistan.

School of Electronic Science and Technology, Xi'an Jiaotong University, Xi'an 710049, China. Email: mkashif@iqra.edu.pk

Syed Saiq Hussain

Manager, Plant Engineering, Feroze1888 Textile Mills, Karachi, Pakistan.

Email: saiqhussain@gmail.com

Muhammad Hassam Shakil Siddiqui

Faculty of Engineering Science and Technology, Iqra University, Karachi 75500, Pakistan. Email: mhd.hasm@gmail.com

Muhammad Daud Abbasi

Faculty of Engineering Science and Technology, Iqra University, Karachi 75500, Pakistan. Email: daud.abbasi@iqra.edu.pk

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>

ABSTRACT

The safety and operational efficiency of aircraft engines depend heavily on the ability to continuously monitor critical components, detect incipient faults, and respond rapidly to emergency conditions. Among the most safety-critical subsystems, the compressor and fuel system play a pivotal role in maintaining optimal thrust and engine performance; their failure during flight can lead to catastrophic consequences. This study proposes an advanced AI-driven architecture specifically designed for real-time monitoring and intelligent fault detection of these systems under emergency operating conditions. The framework integrates high-resolution sensor networks with advanced signal processing techniques to capture and preprocess multidimensional operational data, including pressure, temperature, vibration, and fuel flow parameters. A hybrid machine learning approach combining feature engineering, deep neural networks, and ensemble classifiers is employed to identify anomalies, diagnose fault types, and predict potential failure progression. To enhance accuracy and adaptability, the architecture incorporates a digital twin of the compressor and fuel systems, enabling the simulation of diverse fault scenarios, optimization of detection thresholds, and continuous model learning. The system's layered design consists of a data acquisition layer for high-frequency signal collection, a diagnostic layer for intelligent decision-making, and an emergency response layer that supports flight control systems in initiating corrective measures, including thrust modulation and safe landing protocols. Performance evaluation is conducted using both simulated datasets from the digital twin model and real-world engine operational data obtained from test benches and flight records. Results demonstrate that the proposed system significantly outperforms conventional fault detection and diagnostic methods, achieving detection accuracies above 98%, reducing false alarm rates by over 40%, and enabling fault localization within milliseconds of anomaly onset. Furthermore, the architecture's predictive capabilities facilitate proactive emergency management, minimizing the risk of in-flight engine failure and providing pilots with actionable insights to ensure safe landing procedures. This research establishes a robust, scalable, and adaptive framework that advances the state of the art in aircraft engine health monitoring. The proposed methodology offers significant implications for predictive maintenance, operational reliability, and the design of next-generation mechanical-aerospace safety systems, aligning with the evolving needs of Industry 4.0 and AI-enabled aviation technologies.

Keywords: Aircraft engine compressor, fuel system, fault detection, fault diagnosis, prognostics, real-time monitoring, intelligent health management, emergency operating conditions, artificial intelligence, predictive maintenance, digital twin.

Introduction:

The safety, reliability, and operational efficiency of aircraft propulsion systems have

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>

long been central priorities in aviation research and practice. As air traffic volumes increase and next-generation engine architectures evolve toward higher efficiency and lower emissions, the ability to continuously monitor critical subsystems in real time has become indispensable. Within this domain, the compressor and fuel delivery systems occupy a particularly pivotal role. The compressor provides the necessary pressure ratio for efficient combustion, while the fuel system ensures the accurate metering, pressurization, and delivery of fuel under a wide range of flight and environmental conditions [1]. A malfunction in either of these subsystems manifesting as compressor surge, stall, fuel pump cavitation, line leakage, valve stiction, or icing-induced restriction can have severe consequences, including thrust degradation, unstable operation, and potentially catastrophic in-flight failures. These risks underscore the importance of advanced monitoring and diagnostic systems that can detect anomalies at their inception, localize developing faults with high precision, and trigger emergency responses within milliseconds of anomaly onset. Traditional approaches to engine monitoring have relied heavily on threshold-based fault detection, rule-based expert logic, and simplified observer models embedded within Full Authority Digital Engine Control (FADEC) frameworks. While effective in identifying certain well-characterized anomalies, these conventional systems are constrained in their ability to capture nonlinear interactions, manage transient dynamics, and adapt to unforeseen or evolving failure modes. Emergency operating conditions exacerbate these limitations, as they involve complex, coupled responses that cannot always be represented by static thresholds or simplified models. For example, compressor surge onset often manifests through subtle oscillations in casing pressure, while fuel pump cavitation may first appear as small amplitude fluctuations in flow and acoustic signatures, both of which can be easily overlooked by conventional detection logic. These challenges create a clear research gap, pointing toward the necessity for more adaptive, intelligent, and predictive architectures that can deliver both rapid response and trustworthy interpretation under highly dynamic operating conditions [2]. In recent years, artificial intelligence and machine learning have emerged as transformative tools for health monitoring and prognostics in complex engineering systems. By leveraging high-resolution, multidimensional data from sensors measuring parameters such as pressure, temperature, vibration, and fuel flow, AI-based models are able to uncover hidden patterns that precede fault development. Unlike conventional threshold or model-driven techniques, deep neural networks, ensemble classifiers, and hybrid feature learning frameworks can capture nonlinear relationships and temporal dependencies that characterize abnormal behavior under transient flight regimes. When integrated with physics-informed features such as surge margin estimators, compressor map constraints, and fuel hydraulic equations these models achieve not only predictive accuracy but also a degree of interpretability that is essential for safety-critical applications. The introduction of digital twin technology further strengthens the potential of AI-driven diagnostics. By constructing a high-fidelity virtual replica of the compressor and fuel systems, digital twins make it possible to simulate fault scenarios, optimize detection thresholds, and continuously refine diagnostic algorithms through

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>

online learning. This enables a closed feedback loop between physical and digital systems, where anomalies detected in real time can be validated, contextualized, and extrapolated within the twin environment, thereby enhancing predictive maintenance and emergency management strategies [3]. To illustrate how AI-driven methods contrast with conventional techniques, Table 1 presents a comparative analysis of their capabilities and limitations.

Table 1: Comparative characteristics of conventional fault detection methods and AI-driven architectures

Aspect	Conventional Methods (Threshold/Model-Based)	AI-Driven Fault Detection (Proposed)
Fault detection scope	Limited to predefined faults	Detects both known and emergent faults
Response speed	Often delayed due to thresholding	Millisecond-level decision making
Robustness to noise	Prone to false alarms	Ensemble learning improves resilience
Physics integration	Simplified system representations	Hybrid physics-informed learning
Predictive capacity	Reactive, post-fault response	Predictive, anticipates progression
Certification readiness	Established standards	Emerging, requires explainability

The conceptual framework of the proposed architecture is represented in Figure 1. It illustrates how sensor data streams are acquired in real time, preprocessed through advanced signal conditioning, and subsequently analyzed within a diagnostic layer that integrates machine learning and physics-guided reasoning. The outputs of this diagnostic layer are then interfaced with an emergency response system capable of initiating corrective measures such as thrust modulation and safe landing procedures. A digital twin module forms an essential feedback loop by providing synthetic fault data, refining detection thresholds, and enabling adaptive learning to accommodate new or rare fault scenarios.

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>




Figure 1: Conceptual AI-driven architecture for real-time monitoring and intelligent fault detection of compressor and fuel systems under emergency conditions.

The emergence of such architectures represents a paradigm shift in aircraft engine health management. Preliminary studies have demonstrated detection accuracies exceeding 98 percent, false alarm reductions of more than 40 percent, and decision latencies within tens of milliseconds performance metrics that far surpass those of conventional approaches. These improvements not only enhance operational safety but also provide pilots with actionable insights during emergencies, thereby reducing cognitive load and facilitating timely corrective actions. However, the application of AI in safety-critical aviation systems is not without challenges. Certification bodies require stringent verification of algorithms, explainability of decision-making processes, and resilience against both data corruption and adversarial perturbations [4]. Furthermore, onboard avionics impose constraints on computational power and energy consumption, necessitating efficient model design without compromising accuracy or reliability. In short, the monitoring and fault detection of aircraft engine compressor and fuel systems demand a shift beyond conventional detection frameworks. By uniting artificial intelligence, digital twin technology, and real-time emergency-aware architectures, it is possible to build systems that are not only more accurate but also predictive, adaptive, and certifiable. This paper addresses these needs by presenting an advanced AI-driven architecture specifically designed to achieve rapid anomaly detection, intelligent fault classification, and proactive emergency management. The framework establishes a pathway for predictive maintenance, operational reliability, and next-generation aviation safety systems aligned with the digital transformation of Industry 4.0.

Proposed AI-Driven Framework:

The proposed framework for intelligent fault detection and real-time monitoring of

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>

aircraft engine compressors and fuel systems under emergency conditions is designed as a multi-layered architecture integrating sensor networks, digital twins, and machine learning models. This architecture not only enables rapid anomaly detection but also provides predictive insights into system degradation, thereby enhancing flight safety and reliability.

Architectural Design of the System:

The proposed AI-driven architecture for real-time monitoring and intelligent fault detection of aircraft engine compressor and fuel systems has been conceived as a multi-layered and seamlessly integrated framework that combines advanced sensing technologies, digital twin synchronization, and machine learning intelligence into a unified monitoring and decision-support ecosystem. At its foundation, the architecture incorporates a comprehensive network of physical sensors strategically embedded within the compressor and fuel subsystems. These sensors continuously record vital operational parameters such as temperature gradients, pressure levels, vibration frequencies, fuel flow rates, and acoustic emissions. By capturing these heterogeneous data streams in real time, the system ensures complete situational awareness under both normal and emergency operating conditions, laying the groundwork for predictive analytics and fault detection [5]. Once collected, the raw sensor data are transmitted to the digital twin environment, which constitutes the middle layer of the architecture. The digital twin functions as a high-fidelity virtual replica of the compressor and fuel system, dynamically updated to reflect the exact state of the physical engine. This synchronization enables a dual purpose: firstly, it allows predictive simulations of potential fault scenarios such as compressor surge, blade fatigue, cavitation, or fuel line blockages to be conducted without interfering with actual engine operation; secondly, it provides a continuous benchmark against which real-time sensor readings can be compared. By aligning observed signals with simulated fault signatures, the system can contextualize anomalies, thus transforming ambiguous deviations into meaningful diagnostic indicators. The presence of the digital twin also enables what-if scenario testing, empowering engineers and pilots to visualize the progression of faults under emergency stress conditions and to anticipate their consequences before they escalate into catastrophic events [6]. At the uppermost layer of the system, artificial intelligence models including hybrid machine learning classifiers, anomaly detection networks, and deep reinforcement learning agents serve as the decision-making engine. These models are trained on both historical flight data and synthetic data generated by the digital twin, allowing them to identify patterns that signify the onset of compressor stalls, leaks, or thermal instabilities. Moreover, by leveraging advanced prognostic algorithms, the AI module estimates the remaining useful life (RUL) of critical components, providing actionable recommendations not only for immediate response but also for long-term maintenance planning. The outputs are communicated to cockpit displays in real time and linked with ground-based maintenance management systems, ensuring that the generated alerts are context-sensitive, prioritized by severity, and easily interpretable by both pilots and engineers. To illustrate the interactions among these layers, the

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>

architectural design is depicted in Figure 2, where the flow of data from sensors to the digital twin and finally to the AI-driven decision-support system is presented as an interconnected pipeline. The figure highlights how emergency event simulations are seamlessly integrated with live monitoring, demonstrating the strength of the architecture in managing unforeseen crises.




Figure 2: Proposed AI-driven framework integrating sensor data acquisition, digital twin simulation, and AI-driven fault detection for aircraft engine compressor and fuel system monitoring.

To further clarify the functional contributions of each layer, Table 2 summarizes the system components, their operational roles, and their significance under emergency conditions.

Table 2: System Components, Functions and Emergency Relevance

System Layer	Components	Primary Functions	Emergency Relevance
Sensor Interface	Pressure, temperature, vibration, and fuel flow sensors	Real-time acquisition of physical parameters	Captures abnormal fluctuations indicating stalls, leaks, or surges
Digital Twin Layer	High-fidelity virtual replica of compressor and fuel system	Synchronization, predictive simulations, anomaly contextualization	Enables safe testing of emergency scenarios and fault validation

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>

AI Layer	Machine learning classifiers, anomaly detectors, RUL prediction models	Fault classification, prognostics, decision-making	Provides real-time alerts, severity ranking, and actionable recommendations
----------	--	--	---

The architectural design, by combining physical and virtual layers, enables a continuous feedback loop between the aircraft's operational environment and its predictive intelligence system. This holistic integration provides resilience against uncertainty, ensures faster detection of anomalies, and strengthens the overall safety of aircraft operations in emergency contexts.

Role of AI, Machine Learning, and Digital Twin Integration:

The successful realization of an intelligent fault detection framework for aircraft engine compressor and fuel system monitoring depends largely on the seamless interplay between artificial intelligence (AI), machine learning (ML), and digital twin (DT) technologies. Traditional fault monitoring systems, which rely heavily on static thresholds or linear signal-processing methods, struggle to handle the complexity and nonlinearity inherent in high-speed, high-pressure, and dynamically evolving aerospace systems. To overcome these limitations, the proposed framework adopts a layered intelligence strategy where machine learning algorithms form the first line of anomaly detection, deep learning models enhance temporal and nonlinear feature recognition, and the digital twin environment provides contextual and physics-informed validation of results [7]. Machine learning models such as Support Vector Machines (SVMs), Random Forests, and Gradient Boosted Trees are used to analyze sensor data in real time for detecting subtle deviations from normal operating conditions. Their strength lies in their ability to classify anomalies at an early stage by learning from labeled flight and test data. However, while these models are effective in detecting deviations, they often lack the capacity to generalize to unseen or complex emergency conditions such as compressor surge oscillations or fuel cavitation instabilities [8]. To address this limitation, deep learning architectures, particularly Convolutional Neural Networks (CNNs) and Long Short-Term Memory (LSTM) networks, are integrated into the system. CNNs are leveraged to extract spatial correlations from multi-sensor inputs (e.g., vibration, temperature, and flow patterns), while LSTMs are adept at capturing long-term dependencies and transient temporal events that precede system failures. The digital twin serves as the critical bridging element in this hybrid intelligence framework. Unlike purely data-driven models, the digital twin provides a continuously synchronized, physics-based replica of the real system. This dynamic replica enables the system to test and validate anomalies in real time by comparing sensor-driven predictions with the digital twin's physics-informed state. In addition, the digital twin is used as a data augmentation tool by simulating rare fault conditions that are difficult to capture in operational flight data, such as sudden compressor blade failure or catastrophic fuel system leakage [9]. These synthetic fault scenarios enrich the training dataset for machine learning and deep learning models, significantly improving their

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>

robustness and ability to generalize. The combined integration of AI and digital twin technologies ensures a multi-layer defense system for anomaly detection. Initial ML-based classifiers detect early deviations, DL architectures provide detailed pattern recognition and RUL (Remaining Useful Life) prediction, and the DT validates predictions to reduce false alarms and provide contextual insights. This synergy allows the framework to move beyond reactive fault detection, enabling predictive maintenance and proactive emergency decision support. The interactions between these components are summarized in Table 3, while Figure 3 illustrates their integration within the proposed system framework.

Table 3: Role of AI, ML, and Digital Twin Integration in the Proposed Framework

Component	Function in Framework	Contribution to Fault Detection
Machine Learning Models	Supervised classification of anomalies	Detects early-stage compressor and fuel system faults
Deep Learning Architectures	Sequence modeling of time-series sensor data (CNN, LSTM)	Captures complex, nonlinear, and temporal failure patterns
Digital Twin	Real-time, physics-informed system replication	Provides baseline validation and synthetic training data
Hybrid AI-Twin Integration	Fusion of ML/DL predictions with DT-based insights	Reduces false positives, improves fault localization and emergency accuracy

Through this layered integration of AI, machine learning, and digital twins, the proposed system achieves a balance between data-driven intelligence and physics-based validation, ensuring high accuracy, reduced false alarm rates, and adaptability to novel or previously unseen emergency conditions [10]. This multi-domain synergy not only strengthens system resilience but also provides actionable insights for both cockpit operators and maintenance crews, thereby directly contributing to flight safety and operational efficiency.

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>




Figure 3: Integration of AI, ML, and Digital Twin technologies in the proposed fault detection framework.

Through this layered integration of AI, machine learning, and digital twins, the proposed system achieves a balance between data-driven intelligence and physics-based validation, ensuring high accuracy, reduced false alarm rates, and adaptability to novel or previously unseen emergency conditions. This multi-domain synergy not only strengthens system resilience but also provides actionable insights for both cockpit operators and maintenance crews, thereby directly contributing to flight safety and operational efficiency.

Data Acquisition, Preprocessing, and Feature Extraction Pipeline:

The integrity and performance of the proposed AI-driven fault detection framework depend heavily on the design of the data acquisition and preprocessing pipeline. This pipeline is responsible for capturing, cleaning, and transforming raw sensor data into structured features that machine learning and deep learning models can effectively process. Given the highly dynamic nature of compressor surges, combustion instabilities, and fuel system malfunctions in aerospace propulsion systems, the framework must handle a variety of high-frequency and multi-modal sensor streams with minimal latency while ensuring data fidelity. To achieve this, the system integrates a heterogeneous set of sensors strategically deployed across the propulsion subsystem. Piezoelectric accelerometers are installed to capture high-frequency vibration signals (up to 50 kHz), which are critical for detecting early indications of compressor surge and rotating stall [11]. Thermocouples provide precise measurements of exhaust gas and turbine inlet temperatures at sampling rates of 1–5 kHz, enabling the detection of thermal instabilities. Pressure transducers are placed at critical compressor stages and along the fuel delivery line to monitor fluctuations in airflow and fuel injection

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>

pressure, sampled at frequencies between 5–10 kHz. In addition, flow meters track the instantaneous and cumulative rate of fuel consumption, typically at lower sampling rates (10–20 Hz), since these values vary more slowly compared to vibration or pressure signals. Figure 4 illustrates the integrated data acquisition and preprocessing workflow, highlighting how raw sensor streams are sequentially filtered, normalized, segmented, and transformed into features suitable for AI-based fault detection. This structured pipeline ensures that real-time operational data, despite its inherent noise and heterogeneity, is converted into consistent feature vectors that maintain the physical relevance of the underlying dynamics.




Figure 4: Data acquisition, preprocessing, and feature extraction pipeline for AI-driven compressor and fuel system fault detection.

One of the main challenges in processing raw sensor data is the presence of high-intensity noise induced by aerodynamic turbulence, aircraft structural vibrations, and external environmental conditions such as altitude variations. To address this, the pipeline applies adaptive band-pass filtering to remove irrelevant low-frequency drift and high-frequency electrical noise. Additionally, wavelet denoising techniques are employed to preserve transient fault signatures that are often embedded within broadband signals. After filtering, data normalization is performed to standardize scales across heterogeneous inputs, ensuring comparability between parameters with different physical units (e.g., vibration in g's, temperature in °C, pressure in kPa). Segmentation of time-series signals into overlapping sliding windows (ranging from 100 ms to 1 s, depending on sensor type) allows the extraction of dynamic features while preserving temporal continuity. This segmentation strategy also facilitates the detection of short-lived anomalies such as sudden compressor surges or abrupt drops in fuel pressure, which might otherwise be masked when analyzing long sequences [12]. The feature extraction stage is central to transforming preprocessed signals into meaningful descriptors of system health. Time-domain features such as root mean square (RMS), skewness, and standard deviation provide direct statistical insights into vibration and pressure stability. Frequency-domain features derived from Fast Fourier Transform (FFT) and wavelet decomposition highlight spectral energy distributions, harmonic amplitudes, and resonance frequencies associated with stall or surge phenomena. Statistical features such as kurtosis, Shannon entropy, and cross-sensor correlation

coefficients quantify irregular system behaviors and hidden dependencies among parameters [13]. Finally, hybrid features are generated by combining machine learning–derived residuals with digital twin–based simulation outputs, thereby enriching the feature space with both data-driven and physics-informed descriptors. Table 4 summarizes the major categories of extracted features, their representative parameters, and their role in detecting faults under emergency flight scenarios.

Table 4: Feature Types Extracted from Sensor Data

Feature Category	Example Parameters	Purpose in Fault Detection
Time-Domain	Mean, RMS, Standard Deviation, Skewness	Identifies abnormal fluctuations in vibration/pressure
Frequency-Domain	FFT Peaks, Wavelet Energy, Harmonic Amplitudes	Detects compressor stall frequencies and resonance patterns
Statistical	Kurtosis, Entropy, Correlation Coefficients	Quantifies sudden instability or irregular system behavior
Hybrid Features	Fusion of digital twin residuals + ML features	Improves classification under emergency conditions

By integrating these multi-dimensional features, the framework ensures both sensitivity and robustness in detecting anomalies. Time-domain measures enable quick anomaly flagging, frequency-domain and wavelet features capture more subtle fault-related spectral behaviors, and hybrid AI–digital twin features reduce false positives by grounding data-driven inferences in physical consistency. Collectively, this systematic pipeline establishes the foundation for accurate, real-time monitoring and predictive analytics within the proposed architecture.

Mathematical Modeling and Algorithmic Design:

The mathematical modeling and algorithmic design of the proposed AI-driven framework play a central role in enabling precise anomaly detection, fault prediction, and adaptive decision-making under real-time operating conditions. The first stage of the modeling pipeline involves signal processing for vibration, pressure, and temperature analysis. Vibration signals acquired from piezoelectric accelerometers are decomposed into their frequency components using the Fast Fourier Transform (FFT), defined mathematically as:

$$X(f) = \sum_{n=0}^{N-1} x(n) e^{-j2\pi fn/N}$$

where $x(n)$ represents the discrete vibration signal, N is the total number of samples, and f denotes the frequency index. This transformation allows for the detection of dominant spectral peaks associated with compressor stall frequencies or blade resonance. Similarly, pressure fluctuations are analyzed using power spectral density (PSD) methods, while temperature variations are modeled as time-series processes to capture gradual drifts or sudden deviations indicative of thermal instabilities [14]. Once preprocessed, the extracted feature space is fed into machine learning classifiers

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>

for anomaly detection. The supervised learning stage is modeled by minimizing a loss function, typically the cross-entropy loss for classification tasks, given by:

$$L = - \sum_{i=1}^C y_i \log(p_i)$$

where C represents the number of fault classes, y_i is the ground truth label, and p_i is the predicted probability distribution generated by the classifier. Support Vector Machines (SVMs) employ optimization formulations such as:

$$\begin{aligned} \min (1/2)\|w\|^2 + C \sum \xi_i \\ \text{subject to } y_i(w \cdot x_i + b) \geq 1 - \xi_i \end{aligned}$$

where w is the weight vector, b is the bias term, ξ_i are slack variables, and C is the regularization parameter that balances margin maximization with classification error. In parallel, deep learning architectures such as Long Short-Term Memory (LSTM) networks are applied to model temporal dependencies in multi-sensor data streams. The dynamics of an LSTM unit are defined by its gate equations:

$$\begin{aligned} f_t &= \sigma(W_f [h_{t-1}, x_t] + b_f) \\ i_t &= \sigma(W_i [h_{t-1}, x_t] + b_i) \\ o_t &= \sigma(W_o [h_{t-1}, x_t] + b_o) \\ C_t &= f_t \odot C_{t-1} + i_t \odot \tanh(W_c [h_{t-1}, x_t] \\ &+ b_c) \\ h_t &= o_t \tanh(C_t) \end{aligned}$$

where f_t , i_t , and o_t are the forget, input, and output gates, respectively; C_t represents the memory cell state; h_t is the hidden state; and W , b denote the weight matrices and bias terms. This structure enables the network to capture long-term patterns in sequential sensor data, making it highly effective in predicting imminent faults such as compressor surge or abnormal fuel consumption. The fault detection and prediction model is further enhanced through integration with the digital twin, which introduces residual-based analysis. The residual signal is defined as:

$$r(t) = y_{\text{measured}}(t) - y_{\text{twin}}(t)$$

where $y_{\text{measured}}(t)$ is the sensor output and $y_{\text{twin}}(t)$ is the digital twin prediction under nominal conditions. By continuously minimizing these residuals, the system can adaptively flag anomalies that deviate from both learned statistical patterns and physical system expectations. To summarize the algorithmic and mathematical formulations, the following table 5 outlines the key equations and their role in the framework:

Table 5: Equations and their Role in Framework

Equation / Model	Mathematical	Role in Framework
------------------	--------------	-------------------

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>

	Formulation	
FFT (Vibration Analysis)	$X(f) = \sum x(n) e^{-j2\pi fn/N}$	Frequency-domain detection of compressor instabilities
Cross-Entropy Loss	$L = - \sum y_i \log(p_i)$	Training objective for classification models
SVM Optimization	$\min (1/2)\ w\ ^2 + C \sum \xi_i$	Fault class separation in supervised ML
LSTM Dynamics	f_t, i_t, o_t, C_t, h_t equations	Sequential modeling of temporal dependencies

AI-Based Fault Detection Modeling:

Artificial Intelligence (AI) has emerged as a transformative enabler in modern fault detection frameworks, particularly within safety-critical systems such as aircraft engine compressors and fuel supply mechanisms, where reliability, resilience, and predictive accuracy are indispensable. The proposed AI-based fault detection modeling framework integrates signal processing, feature engineering, and hybrid machine learning algorithms into a unified system that can continuously monitor real-time sensor streams, identify anomalies at an early stage, and provide predictive insights into potential system degradation. Unlike traditional rule-based systems, which often rely on static thresholds and fail to adapt under varying flight conditions, the AI-driven model leverages adaptive learning mechanisms to capture both linear and nonlinear fault patterns in highly dynamic environments [15]. The modeling process begins at the data acquisition stage, where multiple types of sensors including vibration accelerometers, pressure transducers, thermocouples, and fuel flow meters are embedded within the compressor casing and fuel pipelines. These sensors generate high-frequency, multivariate time-series data that reflect the dynamic state of the engine subsystems. Preprocessing techniques such as Fourier Transform (FT), Short-Time Fourier Transform (STFT), and Wavelet Transform (WT) are employed to convert raw time-domain signals into frequency-time spectrograms, which reveal hidden fault signatures that are often imperceptible in the time domain alone. This transformation produces feature-rich datasets that serve as the foundation for subsequent AI modeling. Once features are extracted, both supervised and unsupervised learning methods are employed to construct fault detection models [16]. Supervised machine learning algorithms, including Support Vector Machines (SVM), Random Forests (RF), and Gradient Boosted Decision Trees (GBDT), are trained on labeled datasets derived from experimental fault scenarios such as compressor surge, blade vibration anomalies, fuel leakage, and partial blockage in fuel injectors. These models operate as high-precision classifiers capable of discriminating between different fault categories and normal operating conditions. Meanwhile, unsupervised methods such as clustering algorithms and deep autoencoders play an equally vital role, particularly in detecting novel or previously unseen fault modes [17]. By modeling the normal baseline distribution of operational data, unsupervised models can identify deviations that signal emerging or

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>

unknown anomalies an essential feature for systems exposed to unexpected operating stresses. Deep learning architectures significantly enhance the robustness of this framework by addressing the challenges of nonlinear dynamics, complex interdependencies, and long-range temporal dependencies. Convolutional Neural Networks (CNNs) are deployed to extract hierarchical features from transformed spectrograms of vibration and pressure signals, automatically identifying fault-specific spatial signatures such as compressor stall harmonics or high-frequency blade flutter patterns. To capture the temporal progression of faults, Long Short-Term Memory (LSTM) networks are employed, as they are specifically designed to retain historical dependencies in sequential data. The hybridization of CNNs and LSTMs into a unified CNN–LSTM model further strengthens the fault detection pipeline by simultaneously capturing spatial and temporal dependencies, enabling the system to detect both sudden anomalies and gradual degradation trends [18].

The integration of ensemble learning and probabilistic modeling further elevates the reliability of the framework. Ensemble techniques such as bagging, boosting, and voting classifiers combine multiple weak and strong learners, thereby reducing overfitting risks and enhancing generalizability across different flight scenarios. Bayesian inference techniques, including Gaussian Processes and Bayesian Neural Networks, are incorporated to quantify prediction uncertainty. By assigning probabilistic confidence scores to each prediction, the system not only minimizes false alarms but also provides operators with interpretable alerts that can be prioritized according to severity [19]. This uncertainty-aware decision-making process ensures a balance between sensitivity (detecting true faults) and specificity (avoiding unnecessary alarms). An additional layer of predictive capability is integrated through Remaining Useful Life (RUL) estimation models, which extend fault detection into prognostics. By combining LSTM-based temporal prediction models with regression frameworks such as Deep Survival Analysis, the system estimates the time window before a detected anomaly escalates into critical failure. This allows for timely maintenance scheduling and real-time risk assessment, significantly improving operational safety and reducing unplanned downtime [20]. The complete AI-based fault detection pipeline is illustrated in Figure 5, which demonstrates the flow of data from raw signal acquisition, through feature engineering and AI-based modeling, to the final decision fusion and alert generation module. To further contextualize the role of each algorithm, Table 6 summarizes the AI methods incorporated into the framework, their mathematical formulations, and their specific contributions to compressor and fuel system fault detection.

Online ISSN

3007-3197

Print ISSN

3007-3189


<http://amresearchreview.com/index.php/Journal/about>

Figure 5: Schematic representation of the AI-based fault detection modeling framework integrating sensor data, feature extraction, hybrid deep learning models, ensemble learning, and decision fusion with uncertainty quantification.

This enhanced modeling framework underscores the synergistic role of machine learning, deep learning, and probabilistic inference in establishing a next-generation AI-driven fault detection and prediction system [21]. By combining classification, anomaly detection, uncertainty quantification, and RUL estimation into a unified architecture, the system demonstrates resilience, adaptability, and real-world applicability in the aerospace domain.

Table 6: Summary of AI Algorithms for Fault Detection

Category	Algorithm / Model	Mathematical Formulation	Role in Fault Detection	Strengths
Supervised Learning	Support Vector Machine (SVM)	$f(x) = \text{sign}(\sum_{i=1}^n \alpha_i y_i K(x_i, x) + b)$ $f(x) = \text{sign}(\sum_{i=1}^n \alpha_i y_i K(x_i, x) + b)$	Classifies known faults such as surge, leakage, and stall	High accuracy, interpretable decision boundaries
Supervised Learning	Random Forest	$H(x) = \frac{1}{T} \sum_{t=1}^T H_t(x)$ $H(x) = \frac{1}{T} \sum_{t=1}^T H_t(x)$	Multi-class fault	Robust against

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>

	(RF)	$h_t(x)H(x)=T1\sum_{t=1}^T h_t(x)$	classification across varied conditions	overfitting
Unsupervised Learning	Autoencoder	$(L =$		$X - \hat{X}$
Deep Learning	CNN-LSTM Hybrid	$y_t=LSTM(CNN(X_t))y_t = \text{LSTM}(\text{CNN}(X_{t}))y_t=LSTM(CNN(X_t))$	Captures both spatial (spectrogram) and temporal (time-series) features	High performance in noisy data environments
Ensemble Learning	Gradient Boosting, Voting Classifier	$F_m(x)=F_{m-1}(x)+v h_m(x)F_m(x) = F_{m-1}(x) + \nu h_m(x)F_m(x)=F_{m-1}(x)+v h_m(x)$	Aggregates predictions from multiple learners	Reduces variance, improves reliability
Probabilistic Modeling	Bayesian Neural Networks	$(p(y$	$x) = \int p(y$	$x,w)p(w$
Prognostic Modeling	LSTM-RUL Estimator	$RUL=f(X_{1:t};\theta)RUL = f(X_{1:t}; \theta)RUL=f(X_{1:t}; \theta)$	Predicts remaining useful life of system	Enables predictive maintenance

Aircraft Maintenance Stakeholder Questionnaire:

To ensure that the proposed AI-driven fault detection and predictive maintenance framework aligns with the practical needs of the aviation industry, a structured questionnaire was designed and distributed among key stakeholders, including aircraft maintenance engineers, technicians, system reliability analysts, and operations managers. The primary objective of the questionnaire was to capture insights regarding the limitations of current diagnostic systems, expectations from AI-based solutions, and the practical challenges encountered during fault detection, troubleshooting, and maintenance scheduling in real-world aviation environments. The questionnaire was developed using a combination of closed-ended and open-ended items, allowing both quantitative assessment and qualitative feedback. Closed-ended questions used a Likert scale ranging from 1 (strongly disagree) to 5 (strongly agree), targeting specific areas such as system reliability, diagnostic speed, trust in AI-based decision-making, and integration feasibility with existing maintenance protocols [22]. Open-ended questions

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>

invited participants to elaborate on their experiences with current fault detection methods, their perspectives on adopting digital twin technology, and the operational and ethical concerns associated with AI implementation in critical aircraft systems. To ensure validity, the questionnaire was pilot-tested with a small group of senior engineers before broader distribution. Feedback from this initial trial helped refine the clarity of technical terms, reduce ambiguity in response choices, and balance the length of the survey. A total of 85 stakeholders across different aviation sectors, including commercial airlines, defense aviation units, and aircraft manufacturing firms, were approached for participation. Out of these, 67 completed responses were received, yielding a high response rate of 78.8%, which strengthened the representativeness of the collected data. The design of the questionnaire was structured into four thematic categories: (i) Perceptions of current fault detection systems and their limitations; (ii) Readiness and trust in AI, machine learning, and digital twin integration; (iii) Expected improvements in fault detection accuracy, response time, and maintenance planning; and (iv) Barriers and enablers for successful adoption, including cost implications, regulatory compliance, and workforce training needs [23]. Table 7 presents a representative outline of the questionnaire, showing selected items and their corresponding focus areas.

Table 7: Structure of the Aircraft Maintenance Stakeholder Questionnaire

Category	Sample Question	Response Format	Purpose
Current System Limitations	How often do existing fault detection tools fail to identify early-stage anomalies in compressor/fuel systems?	Likert Scale (1–5)	To assess reliability gaps in traditional methods
AI and Digital Twin Readiness	Do you believe that integrating AI and digital twins can significantly improve fault detection accuracy?	Likert Scale (1–5)	To evaluate openness to emerging technologies
Maintenance Efficiency	How likely is AI-based predictive modeling to reduce unplanned downtime in your operations?	Likert Scale (1–5)	To quantify expected improvements in operational performance
Barriers to Adoption	What challenges do you foresee in implementing AI-driven fault detection in your organization?	Open-ended	To identify technical, economic, and regulatory hurdles
Training and Human Factors	How confident are you in adapting to AI-driven decision support systems in	Likert Scale (1–5)	To measure workforce adaptability and

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>

	your maintenance role?		training requirements
--	------------------------	--	-----------------------

The responses to this questionnaire provided critical feedback for refining the proposed AI framework. For instance, while a majority of stakeholders expressed strong confidence in the potential of AI and digital twin systems to reduce false alarms and enhance predictive accuracy, concerns were raised regarding regulatory certification of AI models and the need for transparent interpretability of automated decisions [24]. Moreover, engineers highlighted that any successful deployment of such systems must be accompanied by specialized training programs and seamless integration with existing maintenance management systems to avoid operational disruptions. The findings from this stakeholder-driven evaluation reinforce the necessity of a balanced approach, where advanced algorithms are complemented by human expertise, domain knowledge, and industry-specific operational practices. By incorporating feedback from these stakeholders, the framework becomes not only technologically sound but also operationally viable, ensuring its acceptance and sustainability in real-world aviation environments.

Methodology:

The proposed AI-driven architecture for real-time monitoring and intelligent fault detection of aircraft engine compressor and fuel systems is designed through a multi-layered methodology that seamlessly integrates high-resolution data acquisition, advanced signal preprocessing, hybrid machine learning models, and digital twin-based validation. The methodology is structured in a way that ensures adaptability, reliability, and responsiveness to emergency operating conditions, allowing for effective detection, diagnosis, and prediction of system faults. The first step involves the data acquisition layer, where high-frequency sensor networks are strategically embedded within the compressor and fuel systems to monitor critical parameters such as pressure, temperature, vibration amplitude, shaft speed, and fuel flow rate. These sensors are capable of generating data at sub-second intervals to capture even the smallest anomalies. The raw signals, however, often contain noise introduced by turbulence, operational vibrations, or sensor imperfections [25]. Therefore, signal preprocessing is applied using advanced filtering techniques such as wavelet transforms, fast Fourier transforms (FFT), and empirical mode decomposition (EMD) to isolate meaningful features while preserving the integrity of transient fault signatures. To bridge the gap between sensor measurements and intelligent decision-making, a feature engineering pipeline is employed. Statistical features (mean, kurtosis, skewness), frequency-domain indicators (spectral energy density, harmonic distortion), and temporal features (time-to-peak, autocorrelation metrics) are extracted. This ensures that the input data fed into machine learning models represent both steady-state performance and transient emergency responses. The extracted features are then standardized and dimensionally reduced using principal component analysis (PCA) to enhance computational efficiency without compromising diagnostic accuracy. The diagnostic layer of the

Online ISSN

3007-3197


Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>

architecture combines deep learning models with ensemble-based approaches for fault detection and classification. A hybrid architecture of Convolutional Neural Networks (CNNs) and Long Short-Term Memory (LSTM) networks is used to simultaneously capture spatial correlations in vibration patterns and temporal progression of anomalies over time. To address class imbalance issues in fault datasets, synthetic minority oversampling techniques (SMOTE) are integrated during model training [26]. Ensemble classifiers such as Random Forests and Gradient Boosting Machines (GBMs) further refine the detection accuracy by aggregating multiple decision paths, thereby reducing variance and minimizing false positives. A novel contribution of this methodology is the integration of a digital twin of the compressor and fuel systems. This virtual replica is constructed using physics-based modeling of thermodynamic cycles, fluid dynamics, and mechanical stresses, combined with AI-driven parameter tuning. The digital twin allows for simulation of diverse fault scenarios such as compressor surge, blade fatigue, fuel leakage, and clogging under variable environmental and emergency conditions. Through these simulations, the system learns fault progression trajectories and dynamically adjusts detection thresholds. This provides a feedback loop that ensures continuous model learning and adaptation, even under evolving flight environments.

The final stage of the methodology involves the emergency response layer, where the outputs from the diagnostic models are fused with flight control logic. Once a fault is detected and classified, decision-support algorithms prioritize the severity of the event and recommend corrective actions such as thrust modulation, emergency fuel rerouting, or activation of safe landing protocols. The integration ensures that pilot workload is minimized during emergencies by providing actionable insights in real time. To illustrate the methodology, Figure 6 presents a schematic overview of the AI-driven architecture, highlighting the layered structure of data acquisition, preprocessing, fault detection, and emergency response. The figure also emphasizes the continuous interaction between the digital twin and real-time diagnostic models, ensuring adaptive and predictive capabilities.



Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>

Figure 6: Proposed AI-Driven Architecture for Real-Time Monitoring and Fault Detection of Aircraft Engine Compressor and Fuel Systems

The effectiveness of the methodology is evaluated using both simulated datasets from the digital twin and real-world datasets from test bench experiments and flight records. The evaluation strategy is summarized in Table 8, which outlines the types of datasets, parameters recorded, data volume, and their role in training, validation, and testing of the proposed system.

Table 8: Dataset Overview for Methodology Validation

Dataset Type	Source	Parameters Monitored	Data Volume	Application Use Case
Simulated Data	Digital Twin Models	Pressure, Temperature, Vibration, Fuel Flow	1.5 TB	Training & Fault Scenario Testing
Test Bench Data	Engine Laboratory Experiments	Shaft Speed, Combustion Efficiency, Flow Rates	800 GB	Model Validation & Threshold Tuning
Flight Recordings	Commercial Aircraft Logs	Vibration Spectrum, Fuel Consumption, Anomaly Logs	2.2 TB	Real-World Evaluation & Emergency Condition Testing

Furthermore, the comparison of the hybrid AI approach against conventional diagnostic methods is shown in Figure 7, where the hybrid framework demonstrates superior performance in terms of fault detection accuracy, false alarm reduction, and response time under simulated and real emergency scenarios.




Figure 7: Comparative Analysis of Proposed Hybrid AI Architecture vs. Conventional Fault Detection Methods

Through this methodology, the research ensures that the developed architecture is not only capable of diagnosing faults with high accuracy but also provides predictive insights to prevent catastrophic failures. The incorporation of hybrid AI techniques, continuous learning via digital twin simulations, and emergency-response integration collectively make the system scalable, robust, and suitable for deployment in next-generation AI-enabled aviation systems.

Results:

The implementation of the proposed AI-driven architecture for real-time monitoring and intelligent fault detection of aircraft engine compressor and fuel systems yielded significant improvements over traditional fault diagnostic methods. The results demonstrated the ability of the system to handle high-dimensional sensor data under emergency operating conditions with remarkable accuracy, efficiency, and robustness. The evaluation was carried out using two distinct datasets: simulated operational data generated through the developed digital twin model and real-world experimental data collected from test benches and flight operational records. By analyzing these datasets, the performance of the proposed architecture was benchmarked against existing statistical and machine-learning-based diagnostic systems. The hybrid machine

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>

learning framework that integrates feature engineering, deep neural networks, and ensemble classifiers was particularly effective in detecting incipient faults. The model achieved an overall fault detection accuracy exceeding 98%, with fault localization achieved within milliseconds of anomaly onset. This level of performance is critical for aviation safety, as even a fraction of a second can determine the feasibility of corrective actions [27]. A comparison between the proposed system and conventional approaches revealed that the architecture not only increased detection sensitivity but also substantially reduced false alarms. As summarized in Table 9, the false alarm rate was reduced by more than 40%, and the accuracy levels consistently surpassed baseline machine learning methods such as Support Vector Machines (SVM) and Decision Trees (DT).

Table 9: Comparative performance of proposed AI-driven architecture vs. baseline methods

Method	Accuracy (%)	Detection Latency (ms)	False Alarm Rate (%)	Fault Localization Precision (%)
Decision Trees (DT)	87.6	12.5	14.3	82.1
Support Vector Machines (SVM)	91.2	10.8	12.7	85.6
Ensemble Classifiers	94.5	9.3	10.2	90.8
Deep Neural Networks (DNN)	96.7	6.4	7.8	94.2
Proposed Hybrid AI Architecture	98.9	3.7	5.1	97.3

The predictive capabilities of the system were further validated through the digital twin model, which simulated various emergency fault scenarios, including compressor surge, blade fatigue, abnormal pressure ratios, fuel pump cavitation, and injector clogging. The architecture successfully identified the onset of each scenario with a high degree of confidence, enabling early fault prediction and proactive response. Figure 8 illustrates the detection accuracy across multiple fault types, highlighting that the proposed system maintained consistently high performance across compressor and fuel system anomalies.

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>




Figure 8: Fault detection accuracy of the proposed AI architecture across multiple fault types

In addition to detection accuracy, one of the most critical outcomes was the evaluation of system responsiveness under real-time operating conditions. The architecture's layered design allowed anomaly detection and emergency response activation within 4 milliseconds on average, far outperforming conventional models that often require 10–15 milliseconds. This rapid response capability was validated through stress-testing the model under simulated high-noise conditions and emergency scenarios. Figure 9 demonstrates the comparative detection latency under different operational stress levels, showing the superiority of the proposed architecture.

Online ISSN

3007-3197

Print ISSN

3007-3189


<http://amresearchreview.com/index.php/Journal/about>

Figure 9: Detection latency comparison under varying operational stress conditions

Another important aspect of the results was the reliability and adaptability of the architecture when transitioning from simulated environments to real-world test bench data. The integration of digital twin simulations with actual sensor measurements proved crucial in enhancing transferability. The system was able to continuously adapt its thresholds based on real-world deviations, thereby reducing overfitting and ensuring robustness across diverse operating conditions. Table 10 provides a detailed breakdown of performance metrics in both digital twin simulations and real-world datasets, underscoring the system's scalability and adaptability.

Table 10: Performance evaluation on digital twin simulation data vs. real-world operational data

Dataset Type	Accuracy (%)	Precision (%)	Recall (%)	F1-Score (%)	False Alarm Rate (%)	Average Latency (ms)
Digital Twin Simulation	99.1	98.7	98.9	98.8	4.6	3.5
Real-World Test Bench	98.3	97.9	98.1	98.0	5.7	4.1
Flight Operational Data	97.8	97.2	97.6	97.4	6.2	4.4

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>

The predictive capacity of the architecture further reinforced its significance in safety-critical environments. By forecasting fault progression trends, the system enabled proactive emergency management protocols, such as thrust modulation and safe landing strategies. These predictive insights not only enhanced in-flight safety but also supported maintenance planning by identifying components approaching critical degradation levels. Collectively, the results highlight the robustness, scalability, and adaptability of the proposed AI-driven architecture. The system consistently achieved detection accuracies above 98%, minimized false alarms, localized faults within milliseconds, and demonstrated resilience across both simulated and real-world operational environments. This performance underscores its potential to significantly advance aircraft engine health monitoring and emergency response, providing a solid foundation for next-generation AI-enabled aviation safety systems.

Challenges and Limitations:

Despite the promising results and demonstrated capabilities of the proposed AI-driven architecture for real-time monitoring and intelligent fault detection of aircraft engine compressors and fuel systems, several challenges and limitations remain that must be acknowledged to provide a balanced perspective on its deployment in real-world aviation environments. One of the foremost challenges is the inherent complexity of aircraft engine operating conditions, where variations in altitude, temperature, atmospheric pressure, and engine load introduce a high degree of uncertainty in sensor data [28]. Although the digital twin framework provides a controlled platform to simulate a wide range of fault scenarios, it cannot perfectly replicate the stochastic and unpredictable variations encountered during actual flight. This discrepancy between simulated and real-world conditions may lead to occasional performance degradation of the diagnostic models, particularly under extreme or rare emergency events that were underrepresented in the training datasets. Another critical limitation lies in the dependency on sensor fidelity and reliability. High-resolution sensors are essential to capture the granular details of vibration signatures, fuel pressure oscillations, and compressor dynamics; however, sensors themselves are prone to calibration drift, noise interference, and hardware failures [29]. A single point of failure in the sensor network can compromise the accuracy of anomaly detection and delay emergency responses. The integration of redundant sensors can partially mitigate this issue, but it increases both system cost and complexity, posing a practical trade-off between safety and economic feasibility. The computational demands of the proposed hybrid machine learning models also present a significant challenge. Deep neural networks and ensemble classifiers require substantial processing power, especially when running in real time on aircraft-embedded hardware. Although the architecture incorporates edge AI acceleration and distributed processing strategies, limitations in onboard computational capacity may restrict the scalability of the system, particularly for next-generation aircraft with larger numbers of sensors and more complex diagnostic requirements.

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>

Another limitation pertains to the adaptability of the digital twin and AI models to engine aging and degradation over time. Aircraft engines are subject to wear-and-tear processes such as material fatigue, corrosion, and thermal stress, which gradually alter their baseline operational characteristics. If the digital twin and diagnostic algorithms are not continuously updated to reflect these evolving conditions, the accuracy of fault detection may diminish. Continuous model retraining and validation using updated flight data are necessary to address this challenge, yet such processes demand significant data availability, computational infrastructure, and regulatory oversight. Data governance and cybersecurity concerns also represent barriers to large-scale adoption. The system relies heavily on the collection and transmission of sensitive operational data, which, if compromised, could lead to both safety risks and confidentiality breaches [30]. Ensuring robust encryption, secure communication protocols, and compliance with international aviation cybersecurity standards is therefore essential, but achieving these safeguards adds additional layers of complexity to the system's design. Table 11 summarizes the key challenges and limitations of the proposed framework, categorizing them according to technical, operational, and regulatory dimensions.

Table 11: Summary of Challenges and Limitations in AI-Driven Fault Detection Architecture for Aircraft Engines

Category	Description	Implications for Deployment
Technical	Sensor failures, calibration drift, and noise sensitivity	Potential false alarms or missed fault detection
Computational	High processing demand of hybrid ML models	Latency in real-time decision-making
Operational	Gap between simulated (digital twin) and real-world conditions	Reduced accuracy under unmodeled flight scenarios
Adaptive	Difficulty in updating models for long-term engine aging and degradation	Need for continuous retraining and validation
Cybersecurity	Risk of data breaches and communication vulnerabilities	Additional security measures and compliance with regulations
Economic	High system cost due to redundant sensors and onboard computing requirements	Barriers to large-scale adoption in commercial aviation

While these challenges and limitations highlight the hurdles in operationalizing AI-based architectures for safety-critical aviation applications, they also provide a roadmap for future research. Addressing them will require the integration of more advanced sensor fusion techniques, lightweight yet robust AI models optimized for real-time inference, adaptive learning mechanisms for handling aging effects, and a holistic

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>

regulatory framework that balances safety, performance, and cybersecurity. Only through overcoming these barriers can the proposed architecture achieve full maturity and be deployed as a trusted component of next-generation aircraft safety systems.

Future Work:

While the proposed AI-driven architecture for real-time monitoring and intelligent fault detection of aircraft engine compressor and fuel systems demonstrates promising performance, there remain several avenues for further development that can extend its applicability, robustness, and operational resilience under real-world conditions. A critical direction for future work lies in expanding the integration of multimodal sensor fusion, incorporating additional data sources such as acoustic emissions, exhaust gas analysis, and high-speed imaging of turbine components. This would not only enhance anomaly detection sensitivity but also enable a more holistic representation of the engine's operational state [31]. Another area of advancement involves improving the adaptability of the digital twin framework. While the current study validates the twin's capability in simulating diverse fault scenarios, future iterations could focus on self-updating twins that continuously learn from real-time flight data, automatically refining fault progression models and dynamically calibrating detection thresholds. Such advancements would allow the system to evolve in tandem with the aging process of engines and adapt to unforeseen degradation patterns. The integration of explainable artificial intelligence (XAI) also represents a pressing research opportunity. Although the system achieves high accuracy in fault detection and classification, providing pilots and engineers with interpretable diagnostic insights remains essential for trust, transparency, and regulatory compliance in aviation systems. Future research should therefore emphasize model explainability, ensuring that AI-driven recommendations can be validated by human experts in high-stakes operational environments [32].

In addition, scalability to fleet-level monitoring offers another prospective enhancement. Extending the framework to analyze and correlate operational data across multiple aircraft could enable predictive fleet health management, identifying systemic risks, optimizing maintenance schedules, and enhancing overall airworthiness. This would align with the vision of Industry 4.0 and digital aviation ecosystems where connected aircraft collaboratively improve safety and efficiency [33]. From a technical standpoint, future work could also focus on embedding the proposed architecture into edge-computing platforms onboard aircraft. This would reduce reliance on ground-based processing and ensure that fault detection and emergency response mechanisms are executed with minimal latency, even under communication constraints. Furthermore, advances in hardware accelerators such as neuromorphic processors and quantum-inspired architectures could be explored to handle increasingly complex diagnostic tasks under stringent real-time requirements. Finally, addressing certification and regulatory pathways remains an essential trajectory for future research [34]. The adoption of AI-driven architectures in safety-critical aviation systems requires compliance with standards such as DO-178C and ARP4754A. Therefore, future studies should explore methods for formally verifying AI models, establishing

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>

safety cases, and demonstrating robustness under extreme and adversarial operational conditions. Taken together, these directions highlight the potential for continuous refinement and expansion of the proposed framework, paving the way toward intelligent, autonomous, and resilient health monitoring systems for next-generation aircraft engines [35]. By bridging advancements in AI, digital twins, and aerospace engineering, future developments can further revolutionize predictive maintenance, emergency management, and the safety assurance of flight-critical systems.

Conclusion:

The development of an advanced AI-driven architecture for real-time monitoring and intelligent fault detection of aircraft engine compressor and fuel systems under emergency operating conditions represents a significant step toward transforming aviation safety and reliability. By integrating advanced deep learning models, digital twin simulations, and adaptive sensor-based diagnostics, the proposed framework has demonstrated the capacity to identify early-stage anomalies, predict fault progression, and provide actionable insights with high accuracy and minimal latency. This capability is particularly crucial in emergency operating conditions where rapid decision-making and proactive fault management can prevent catastrophic failures and safeguard both human lives and aircraft assets. The findings of this study underscore the advantages of shifting from conventional reactive maintenance strategies toward predictive and condition-based approaches that leverage artificial intelligence. The incorporation of real-time data streams from compressors and fuel systems not only improves fault detection sensitivity but also enhances situational awareness for pilots and ground engineers. Furthermore, the architecture's capacity to simulate and validate different fault conditions through digital twins demonstrates its adaptability to complex and dynamic operating environments. While challenges remain in terms of system scalability, explainability of AI decisions, and compliance with aviation certification standards, the research provides a strong foundation for the integration of intelligent health monitoring systems in next-generation aircraft. By addressing these limitations and pursuing the outlined future directions such as multimodal sensor fusion, fleet-wide predictive analytics, and explainable AI the proposed framework has the potential to evolve into a comprehensive, industry-ready solution. Ultimately, the presented research reinforces the critical role of artificial intelligence in modern aerospace engineering. By enabling real-time fault detection and robust emergency response mechanisms, the AI-driven framework not only contributes to enhanced operational safety but also paves the way for more sustainable, efficient, and resilient aviation systems. This advancement is aligned with the broader vision of digital transformation in aerospace, where intelligent systems play a central role in ensuring safety, optimizing maintenance cycles, and shaping the future of autonomous and connected aircraft operations.

References:

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>

- Kabashkin, I., Perekrestov, V., & Pivovarov, M. (2025). AI-Driven Fault Detection and Maintenance Optimization for Aviation Technical Support Systems. *Processes*, 13(3), 666.
- Enemosah, A. (2021). Intelligent decision support systems for oil and gas control rooms using real-time AI inference. *International Journal of Engineering Technology Research & Management*, 5(12), 236-244.
- Amjad, M. H. H., Chowdhury, B. R., Reza, S. A., Shovon, M. S. S., Karmakar, M., Islam, M. R., ... & Ripa, S. J. (2025). AI-Powered Fault Detection in Gas Turbine Engines: Enhancing Predictive Maintenance in the US Energy Sector. *Journal of Ecohumanism*, 4(4), 658-678.
- Ayeni, O. (2025). Integration of Artificial Intelligence in predictive maintenance for mechanical and industrial engineering. *International Research Journal of Modernization in Engineering Technology and Science*, 7(3), 1-23.
- SHAMIM, M., RAHAMAN, M., & Ruddro, R. A. (2025). Smart Diagnostics in Industrial Maintenance: A Systematic Review of Ai-Enabled Predictive Maintenance Tools and Condition Monitoring Techniques.
- Moldamurat, K., La Spada, L., Zeeshan, N., Bakyt, M., Kuanysh, A., bi Zhanibek, K., & Tilenbayev, A. (2025). AI-Enhanced High-Speed Data Encryption System for Unmanned Aerial Vehicles in Fire Detection Applications. *Journal of Robotics and Control (JRC)*, 6(4), 1899-1937.
- Feroz, E. S., Zaidi, S. K. A., Ahmad, B., Rafique, M., Zadrán, S., & Hassan, M. (2025). DESIGNING AN INTELLIGENT SMART VTOL DRONE USING FLYSKY TRANSMITTER AND PIXHAWK CONTROLLER FOR HIGH-RISK RESCUE AND MILITARY OPERATIONS. *Spectrum of Engineering Sciences*, 3(3), 1-16.
- Kabashkin, I. (2024). The iceberg model for integrated aircraft health monitoring based on AI, blockchain, and data analytics. *Electronics*, 13(19), 3822.
- Joung, B. G. (2025). Prognostics and Fault Diagnosis for Manufacturing Equipment using Machine Learning (Doctoral dissertation, Purdue University Graduate School).
- Priya, S. S., Sanjana, P. S., Yanamala, R. M. R., Amar Raj, R. D., Pallakonda, A., Napoli, C., & Randieri, C. (2025). Flight-Safe Inference: SVD-Compressed LSTM Acceleration for Real-Time UAV Engine Monitoring Using Custom FPGA Hardware Architecture. *Drones*, 9(7), 494.
- Soomro, A. A., Arshad, J. A., Saira, A. N., Khalil, A., Qamar, S., Khawer, S. K., & Jamil, K. NEXT-GENERATION DRONE-BASED EMERGENCY SYSTEMS: AI-POWERED UAV FRAMEWORK FOR ENCRYPTED COMMUNICATION AND MULTIMODAL DATA CLASSIFICATION IN EMERGENCY DETECTION AND RESPONSE SYSTEMS.
- Bardis, K., Avdelidis, N. P., Ibarra-Castaneda, C., Maldague, X. P., & Fernandes, H. (2025). Advanced diagnostics of aircraft structures using automated non-invasive imaging techniques: a comprehensive review. *Applied Sciences*, 15(7), 3584.
- Ali, M. A. B. (2025). Advanced Predictive Maintenance Strategies for Green

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>

- Transportation Systems Implementing AI and Internet of Things Technologies. *Journal of Artificial Neural Networks and Deep Learning Applications*, 15(3), 1-18.
- Eswararaj, D., Koppada, L. R., & Bodala, R. S. (2025). Quantifying the Influence of Artificial Intelligence and Machine Learning in Predictive Maintenance for Vehicle Fleets and Its Impact on Reliability and Cost Savings.
- Fu, H., Rao, J., Deng, F., Wang, Y., Zhao, B., Liu, Z., ... & Xu, L. (2025). AIoT: Artificial Intelligence and the Internet of Things for Monitoring and Prognosis of Systems and Structures. *IEEE Transactions on Instrumentation and Measurement*.
- Ogunnowo, E. O. A Conceptual Framework for Digital Twin Deployment in Real-Time Monitoring of Mechanical Systems.
- Ajayi, R. (2025). Integrating IoT and cloud computing for continuous process optimization in real-time systems. *Int J Res Publ Rev*, 6(1), 2540-2558.
- Shen, Z., Arraño-Vargas, F., & Konstantinou, G. (2024). Artificial intelligence and digital twins in power systems: Trends, synergies and opportunities: [version 2; peer review: 2 approved]. *Digital Twin*, 1(3), 11.
- Kabashkin, I. (2025). Framework for Addressing Imbalanced Data in Aviation with Federated Learning. *Information*, 16(2), 147.
- Annapareddy, V. N. (2021). Machine Learning Algorithms for Real-Time Fault Detection and Performance Enhancement in Solar Energy Systems. Available at SSRN 5262966.
- Aribisala, A., & Kelechi, F. M. (2025, August). Enhancing Asset Integrity Management Using AI in the Yoga Gas Plant, Niger Delta Region of Nigeria. In *SPE Nigeria Annual International Conference and Exhibition* (p. D022S025R006). SPE.
- Chukwunweike, J., & Salaudeen, H. D. Advanced Computational Methods for Optimizing Mechanical Systems in Modern Engineering Management Practices.
- Amin, A. A., & Mahmood-ul-Hasan, K. (2019). Hybrid fault tolerant control for air–fuel ratio control of internal combustion gasoline engine using Kalman filters with advanced redundancy. *Measurement and Control*, 52(5-6), 473-492.
- Srivastava, I., Bhat, S., & Singh, A. R. (2024). Fault diagnosis, service restoration, and data loss mitigation through multi-agent system in a smart power distribution grid. *Energy Sources, Part A: Recovery, Utilization, and Environmental Effects*, 46(1), 16431-16456.
- Padinhakara, M. J. (2025). Vehicular data management at scale: Architectural frameworks for cars as mobile data centers. *World Journal of Advanced Engineering Technology and Sciences*, 15(3), 752-758.
- Liang, C., Li, X., Niu, W., & Zhang, Y. (2025). Internet of Things Driven Digital Twin for Intelligent Manufacturing in Shipbuilding Workshops. *Future Internet*, 17(8), 368.
- Aikins, S. A., Avevor, J., & Enyojo, L. A. (2024). Optimizing Thermal Management in Hydrogen Fuel Cells for Smart HVAC Systems and Sustainable Building Energy Solutions. *International Journal of Scientific Research and Modern Technology*

Online ISSN

3007-3197

Print ISSN

3007-3189

<http://amresearchreview.com/index.php/Journal/about>

- (IJSRMT) Volume, 3.
- Iqbal, M. S., & Amin, A. A. (2022). Genetic algorithm based active fault-tolerant control system for air fuel ratio control of internal combustion engines. *Measurement and Control*, 55(7-8), 703-716.
- Ali, G., Mijwil, M. M., Adamopoulos, I., & Ayad, J. (2025). Leveraging the internet of things, remote sensing, and artificial intelligence for sustainable forest management. *Babylonian Journal of Internet of Things*, 2025, 1-65.
- Trigka, M., & Dritsas, E. (2025). Wireless Sensor Networks: From Fundamentals and Applications to Innovations and Future Trends. *IEEE Access*.
- Stevens, R., Taylor, V., Nichols, J., Maccabe, A. B., Yelick, K., & Brown, D. (2020). Ai for science: Report on the department of energy (doe) town halls on artificial intelligence (ai) for science (No. ANL-20/17). Argonne National Lab.(ANL), Argonne, IL (United States).
- Rataj, M., LODI, C., Zawieska, J., Stepniak, M., CHEIMARIOTIS, I., Grosso, M., ... & Marotta, A. (2025). New and Emerging Transport Technologies and Trends in European Research and Innovation Projects 2024.
- Iqbal, M. S., & Amin, A. A. (2022). Genetic algorithm based active fault-tolerant control system for air fuel ratio control of internal combustion engines. *Measurement and Control*, 55(7-8), 703-716.
- Rataj, M., LODI, C., Zawieska, J., Stepniak, M., CHEIMARIOTIS, I., Grosso, M., ... & Marotta, A. (2025). New and Emerging Transport Technologies and Trends in European Research and Innovation Projects 2024.
- Ray, P. P. A Review of TRiSM Frameworks in Artificial Intelligence Systems: Fundamentals, Taxonomy, Use Cases, Key Challenges and Future Directions. *Authorea Preprints*.
- Abd El-Nabi, S., Ibrahim, A. F., El-Rabaie, E. S. M., Hassan, O. F., Soliman, N. F., Ramadan, K. F., & El-Shafai, W. (2025). Driver drowsiness detection using swin transformer and diffusion models for robust image denoising. *IEEE Access*.